


Standard and Ground Terminal Blocks

Compression clamp

M 16/12 Spacing 12mm




Characteristics		IEC NFC VDE	UL	CSA
Wire size mm ² / AWG	Solid Wire	0.5 - 25*	14-4AWG	14-4AWG
	Stranded Wire	0.5 - 16*		
Rated voltage	V	800	600	600
Rated current	A	85	85	100
Rated wire size	mm ² / AWG	16mm ²	4AWG	4AWG
Wire stripping length	mm / inches	14mm / .55"		
Recommended torque	Nm / lb.in	1.2-1.4 Nm / 10.6-12.3 lb-n		

Selection

Body Colour	Type	Order Code	Pack
● Grey	M 16/12	0115 129.14	20
● Blue	M 16/12.N	0125 129.16	20
● Yellow	M 16/12	0105 129.23	20
● Beige VO	M 16/12 VO	0195 129.15	20
● Green+yellow (with contact rail)	M 16/12.P	0165 130.23	20
● Green+yellow VO (with contact rail)	M 16/12.P VO	0195 130.12	20
● Yellow+green (without contact rail)	M 16/12.PI	0165 453.23	20

M 35/16 Spacing 16mm



Characteristics		IEC NFC VDE	UL	CSA
Wire size mm ² / AWG	Solid Wire	1 - 50	16-0AWG	16-0AWG
	Stranded Wire	1 - 35		
Rated voltage	V	800	600	600
Rated current	A	125	150	140
Rated wire size	mm ² / AWG	35mm ²	0AWG	0AWG
Wire stripping length	mm / inches	17mm / .67"		
Recommended torque	Nm / lb.in	2.8-3 Nm / 24.3-26.1 lb-in		

Selection

Body Colour	Type	Order Code	Pack
● Grey	M 35/16	0115 124.07	20
● Blue	M 35/16.N	0125 124.01	20
● Yellow	M 35/16	0105 124.16	20
● Beige VO	M 35/16 VO	0195 124.00	20
● Green+yellow (with contact rail)	M 35/16.P	0165 111.14	20
● Green+yellow VO (with contact rail)	M 35/16.P VO	0195 111.03	20
● Yellow+green (without contact rail)	M 35/16.PI	0165 454.24	20

*Note	M16/12.P	M35/16.P
Solid Wire	4-25 mm ² 14-4 AWG	4-50mm ² 12-0 AWG
Stranded Wire	4-16mm ²	4-35mm ² 12-2 AWG

[Return to main index](#)