



**Product Description:** SET IN 3W fixed 120° IP67 Rectangle Recessed Wall light White 4000K

Recessed wall & ceiling EUROPOLE SET IN 6.2 rectangle, fixed, white, white 3000K, CRI>70, 3W, 59lm (18.33lm/W), symmetrical opal diffuser 120°, 230VAC. Protection class I, IP67, IK08, insulator compatible: no, wired 0.3m. Lifespan: 30,000 hours. Dimmable: No. Flange dimension: 155x76mm. Installation dimension: 135x71mm. Material: aluminum body and bezel. Surface treatment: anti-corrosion treatment. Operating temperatures: -20°C/+40°C. Walkover: No.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
37220	3	3000	59	20	120	White	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Aluminium body and bezel
- Pre-wired with 0.3m of cable
- 30000hrs lifetime
- 5 year warranty
- SDCM5

Product Specs:

Input Voltage	~230V AC	Input Frequency	50/60HZ
IP Rating	IP67	Lifetime L70 (hrs)	30000hrs
IK Rating	IK08	Width (mm)	76
Height (mm)	155	Product Type	Wall Lights
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

## Compliance & Approvals:

## Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.