

Product Code: DPSS550WH

Description: 13A Ingot Fused Connection Unit With Optional Flex Outlet



General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)	
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Rounded Profile	
Finish	Stainless Steel	
Insert Colour	White	
Gasket Colour	White	
Materials	Front Plate: Stainless Steel	Insert & Housing: Urea
	Fuse Drawer Cover: Stainless Steel	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	No	
Twin Earth Terminals	Yes	
Product Marking	Fused	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-4: 2016 +A1: 2018 BS 1362: 1973 +A3: 2021	

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.