



Freska



Part of the Downlights product category

Model	Freska CCT Downlight 1 White
Code	AFRE1/1
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	9W
Operating Temp	-20°C - 40°C
Lumens Delivered	840lm (4000K)
lm/W	105lm/w
CCT	3000/4000/6000K
UGR	25
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.2376 kg
Colour / Finish	White
Diameter	137 mm
Height	24 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.88
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Economic ultra-slim circular LED performance downlight suitable for education, commercial, healthcare and retail applications
- CCT selectable between 3000K, 4000K and 6000K
- Ideal for use in areas with shallow ceiling void
- Edge lit providing excellent uniform illumination
- Triac dimmable as standard





Freska



Part of the Downlights product category

Model Freska CCT Downlight 1 White

Code AFRE1/1

Application Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

