essentials[™]

Technical Specification

Product Code: CL012 Description: 10AX 2 Gang 2 Way Plate Switch



General Information

Dimensions 80mm (W) x 80mm (H) x 42mm (D)

Finish Metal Clad Grey
Insert Colour White (WH)

Materials Front Plate & Mounting Box: Electrophoretically

Coated Steel

Rear Housing: Nylon

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V∼ 50Hz

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 60.3mm
Terminal Size 3.5mmø
Terminal Torque 0.5Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²

Two Way Yes

Back Box Depth 40mm Supplied

Termination Type Screw
Earth Terminal Provided Yes

Back Box Knockouts 5 x 20mm (2 on top, 1 on bottom, 1 on each side)

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

Insert & Rocker Switch: Urea

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Earth Strap: Mild Steel





