

Product Code: CL025

Description: 10AX 1 Gang Intermediate Plate Switch



### General Information

|                                |  |  |
|--------------------------------|--|--|
| <b>Dimensions</b>              | 80mm (W) x 80mm (H) x 42mm (D)                               |  |
| <b>Finish</b>                  | Metal Clad Grey  |  |
| <b>Insert Colour</b>           | White (WH)   |  |
| <b>Materials</b>               | Front Plate & Mounting Box: Electrophoretically Coated Steel | Insert & Rocker Switch: Urea             |
|                                | Rear Housing: Nylon  | Terminals: Brass                         |
|                                | Terminal Screws: Steel & Yellow Passivated                   | Contacts: Silver "on-lay" Copper / Brass |
|                                | Internal Busbars: Formed Pressed Brass                       | Earth Strap: Mild Steel                  |
| <b>Maximum Voltage</b>         | 250V~ 50Hz   |  |
| <b>Load Rating</b>             | 10AX (Suitable for Inductive Loads)                          |  |
| <b>Plate Fixing Centres</b>    | 60.3mm   |  |
| <b>Terminal Size</b>           | 3.5mmø   |  |
| <b>Terminal Torque</b>         | 0.5Nm  |  |
| <b>Terminal Capacity</b>       | 4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>             |  |
| <b>Intermediate</b>            | Yes  |  |
| <b>Back Box Depth</b>          | 40mm Supplied  |  |
| <b>Termination Type</b>        | Screw  |  |
| <b>Earth Terminal Provided</b> | Yes  |  |
| <b>Back Box Knockouts</b>      | 5 x 20mm (2 on top, 1 on bottom, 1 on each side)             |  |
| <b>Operational Temperature</b> | -5°C to +40°C  |  |
| <b>Warranty</b>                | 10 Years   |  |
| <b>Standards</b>               | BS EN 60669-1:1999 +A1:2002 +A2:2008                         |  |

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

