

Product Code: CL050

Description: 13A Fused Connection Unit With Optional Flex Outlet



General Information

Dimensions	80mm (W) x 80mm (H) x 42mm (D)	
Finish	Metal Clad Grey	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Fuse Drawer & Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz	
Load Rating	13A	
Plate Fixing Centres	60.3mm	
Terminal Size	5mmø	
Terminal Torque	2.0Nm	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²	
Switched	No	
Twin Earth Terminals	Yes	
Fuse Fitted	13A (BS 1362)	
Flex Outlet	Yes (10mmø Through Front of the Plate)	
Back Box Depth	40mm Supplied	
Termination Type	Screw	
Earth Terminal Provided	Yes	
Back Box Knockouts	5 x 20mm (2 on top, 1 on bottom, 1 on each side)	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS 1363-4: 2016 +A1: 2018 BS 1362:1973	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.