essentials[™]

Product Code: CL053

Technical Specification





General Information

80mm (W) x 80mm (H) x 42mm (D) **Dimensions**

Metal Clad Grey Finish

Materials Front Plate & Mounting Box: Electrophoretically

Coated Steel

Neon Lens: Polycarbonate

Terminal Screws: Steel & Yellow Passivated

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A Plate Fixing Centres 60.3mm **Terminal Size** 5mmø **Terminal Torque** 2.0Nm

Terminal Capacity 3 x 2.5mm² or 2 x 4mm²

Switched No Twin Earth Terminals Yes **Neon Indicator** Yes (Red) Fuse Fitted 13A (BS 1362)

> Flex Outlet Yes (10mmø Through Front of the Plate)

Back Box Depth 40mm Supplied

Termination Type Earth Terminal Provided Yes

Back Box Knockouts 5 x 20mm (2 on top, 1 on bottom, 1 on each side) -5° C to $+40^{\circ}$ C

Operational Temperature

Warranty 10 Years

BS 1363-4: 2016 +A1: 2018 **Standards**

BS 1362:1973

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Insert, Fuse Drawer & Housing: Urea

Internal Busbars: Formed Pressed Brass

Terminals: Brass