






Technical Specification

Product Code: CMA618

Description: 3 Tier MiniGrid® Unfurnished Plate & Yokes - 18 Apertures



General Information Plate Dimensions (mm MiniGrid Plate (Gang MiniGrid Single Width Module Quantit MiniGrid Double Width Module Quantit Styl Finis Material Anti Microbial Certifie Termination Typ Modular Rocker Switche Yoke Earth Terminal Supplie Yoke Require Minimum Back Box Depth (mm Ingress Protectio Operational Temperature (°C)	 146 (W) x 214 (H) x 9.5 (D) 18 18 (3 x 6) 9 Mode Polar White Front Plate: Urea Terminal Housing: Urea Terminal Screws: Steel & Yellow Passivated Yes Screw Yes One Earth On Each Yoke No 47 IP20 -5 to +40 	Earthing Yoke: Mild Steel Terminals: Brass
Standards BS 55	733: 2010 +A1: 2014	
diagr Bare All wh prope prope All p envel bacte	that the mains supply is isolated before commencing installation and refer to the circuit m with the relevant product. arth cables must always be covered with appropriate sleeving and wired to the earth terminal. e moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent ties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral ties against enveloped and non-enveloped viruses. ducts have been independently tested with 99.9% of enveloped viruses and 92% of non- bed viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of a - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.	