

Technical Specification



Electronics: PCB & Electronic Components

Signal Transmission Frequency 400MHz

Product Code: CSP010 Description: Smart Gateway Hub



General Information

Dimensions (mm) 90 (L) \times 90 (W) \times 23 (D)

Finish White

Materials Housing: Polycarbonate

Rated Voltage (DC) 1.8 - 3.3

Protocol Zigbee

Wireless Technology WIFI 801.11 b/g/n

System Requirements Mobile Device Running IOS 8 or Higher or Android 4.1x or Higher.

Indicator Colour Green Ingress Protection IP20

Working Humidity 10%-90%RH (Non-condensing)

Operational Temperature (°C) -10 to +55

Warranty (Years)

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Required for controlling Zigbee devices via the app and voice control

Overview of how many devices can be connected:

Hardwired Connected Devices Only: 256
Pattern Payaged Devices Only: (With vd. Llub)

Battery Powered Devices Only (With x1 Hub): 32

Mix of Both Battery Powered and Hardwired: 256 with a Maximum of 62 Battery Powered Devices NOTE: If you are pairing more than 128 devices within the range, please contact technical support on

+44 (0) 1827 63454

Components Supplied Smart HubUK Plug-in Power Adaptor Ethernet CableInstruction Manual

Programming Information Once paired to the app all Zigbee devices and voice control can be added.

