

**Product Code:** CSP033

**Description:** Smart Temperature & Humidity Sensor



### General Information

<b>Dimensions (mm)</b>	37 (Dia.) x 11.6 (D)	
<b>Finish</b>	White	
<b>Materials</b>	Housing: Polycarbonate	Electronics: PCB & Electronic Components
<b>Rated Voltage (DC)</b>	3	
<b>Battery Type</b>	CR 2032 (Supplied)	
<b>Battery Lifetime (Approx.)</b>	1 Year (Dependent On Use)	
<b>Protocol</b>	Zigbee	<b>Signal Transmission Frequency</b> 2.4GHz
<b>Temperature Accuracy (%)</b>	±3	
<b>Indicator Colour</b>	Blue	
<b>Ingress Protection</b>	IP20	
<b>Working Humidity</b>	0%-100%RH (Non-condensing)	
<b>Operational Temperature (°C)</b>	-10 to +50	
<b>Warranty (Years)</b>	1	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Control linked receivers through the ClickSmart+ app  
Send activation alerts to your phone

**Components Supplied** Smart Temperature & Humidity Sensor CR 2032 Battery Reset Key Instruction Manual

**Installation Overview** Suitable for ceiling or wall mounting.  
Self-adhesive pad applied ready for installation.

**Programming Information** With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.