



Connectors, metric and PG, polyamide thread

Type LWD & LND

Type LWD - Connector 90° elbow, metric thread

	Order no. black, IP66	Order no. grey, IP66	Thread metric	Fits to conduit size		Thread length (mm)	External dimensions (mm)	
				NW	Metric			
	LWD, patent	ALWD-M120	SLWD-M120	M12 x 1.5	10	12	11.0	33.0 x 36.5
		ALWD-M160	SLWD-M160	M16 x 1.5	10	12	11.0	33.0 x 38.5
		ALWD-M162	SLWD-M162	M16 x 1.5	12	16	11.0	37.5 x 43.0
		ALWD-M202	SLWD-M202	M20 x 1.5	12	16	11.0	37.5 x 45.0
		ALWD-M207	SLWD-M207	M20 x 1.5	17	20	11.0	42.0 x 50.5
		ALWD-M257	SLWD-M257	M25 x 1.5	17	20	12.0	43.0 x 53.0
		ALWD-M253	SLWD-M253	M25 x 1.5	23	25	12.0	52.5 x 59.0
		ALWD-M323	SLWD-M323	M32 x 1.5	23	25	15.0	56.0 x 62.5
		ALWD-M329	SLWD-M329	M32 x 1.5	29	32	15.0	62.5 x 69.0
		ALWD-M409	SLWD-M409	M40 x 1.5	29	32	19.0	66.5 x 72.0
		ALWD-M406	SLWD-M406	M40 x 1.5	36	40	19.0	76.0 x 83.0
		ALWD-M506	SLWD-M506	M50 x 1.5	36	40	19.0	76.0 x 87.0
		ALWD-M508	SLWD-M508	M50 x 1.5	48	50	19.0	89.0 x 92.5
		ALWD-M638	SLWD-M638	M63 x 1.5	48	50	19.0	89.0 x 99.0

Type LND - Connector straight, PG thread

	Order no. black, IP66	Order no. grey, IP66	Thread PG	Fits to conduit size		Thread length (mm)	Overall length (mm)	
				NW	Metric			
	LND, patent	ALND-P070*	SLND-P070*	07	10	12	7.0	44.0
		ALND-P090	SLND-P090	09	10	12	11.0	34.0
		ALND-P092*	SLND-P092*	09	12	16	8.0	50.0
		ALND-P110	SLND-P110	11	10	12	8.0	45.5
		ALND-P112	SLND-P112	11	12	16	11.0	38.0
		ALND-P132	SLND-P132	13.5	12	16	11.0	38.0
		ALND-P137	SLND-P137	13.5	17	20	11.0	41.0
		ALND-P167	SLND-P167	16	17	20	11.0	41.0
		ALND-P213	SLND-P213	21	23	25	12.0	45.5
		ALND-P299	SLND-P299	29	29	32	12.0	47.5
		ALND-P366	SLND-P366	36	36	40	13.0	54.5
		ALND-P488	SLND-P488	48	48	50	13.0	55.0

*These products will be delivered with a thread adapter