



Physical data

Width	1 mm / 0.039 inches
Height	69.5 mm / 2.736 inches
Depth	30.5 mm / 1.201 inches

Material data

Note (material data)	Information on material data can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.066 MJ
Weight	2.3 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) Stück
Country of origin VKOrg Germany	DE
GTIN	4055143975452
Customs tariff number VKOrg Germany	85389099990

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 2104-1291



Documentation

Additional Information

Technical Section

pdf
2142.18 KB



Bid Text

2104-1291

docx
20.33 KB



2104-1291

xml
2.91 KB



CAD/CAE-Data

CAD data

2D/3D Models
2104-1291



CAE data

ZUKEN Portal
2104-1291





Physical data

Width	1 mm / 0.039 inches
Height	74.8 mm / 2.945 inches
Depth	32.9 mm / 1.295 inches

Material data

Note (material data)	Information on material data can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.073 MJ
Weight	2.4 g

Commercial data

eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) Stück
Packaging type	Box
Country of origin VKOrg Germany	DE
GTIN	4055143745383
Customs tariff number VKOrg Germany	85389099990

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2106-1291



Documentation

Additional Information

Technical Section

pdf
2142.18 KB



Bid Text

2106-1291

19.02.2019

xml
2.51 KB



2106-1291

08.08.2018

docx
14.24 KB



CAD/CAE-Data

CAD data

2D/3D Models
2106-1291



CAE data

EPLAN Data Portal
2106-1291



ZUKEN Portal
2106-1291

