

Luminaires | Fire Rated Downlights

R6™ Colour & Wattage Switchable Adjustable Fire Rated Downlight with FastRFix

AU-R62W/CWS



Photometrics

Wattage	3.5 / 5.5
Lumens	455-745
Lm/W	123 / 130 / 130 / 130
Beam Angle	60
Colour Temperature	2700 / 3000 / 4000 / 6500
Ra	90

Product Features

Brand	Aurora
IP Rating	IP65
L80 Hours	50,000
Lifetime Class	L80 B50
Dimmable	Triac
Warranty	5 Years
Country of Origin	CH
Barcode	5056102075687

Electrical Specification

Input Voltage (Min)	220
----------------------------	-----

Input Voltage (Max)	240
Output Voltage	DC
Input Voltage Type	AC
Power Factor	0.8
Surge Protection (kV)	1500
Protection Class	Class 2
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	650

Physical Attributes

Height (mm)	63
Overall Diameter (mm)	88
Cutout Diameter Max. (mm)	70
Material	Polycarbonate & Pressed Steel
Optic Material	Clear Multifaceted
Mount Options	Recessed
Finish Colour	White

Features

Marketing Feature 1	Certified for solid timber, I-joist, and metal web joist ceilings
Marketing Feature 2	FastRFix connector with LENNEL terminals for ease of installation
Marketing Feature 3	Easy glide soft springs suitable for double plaster board ceilings
Marketing Feature 4	Low profile design for use in shallow ceilings
Marketing Feature 5	Supplied with white IP65 polycarbonate bezel
Marketing Feature 6	CRI90 for optimized colour rendering
Marketing Feature 7	Energy Rating C
Marketing Feature 8	L80B50 50,000hrs
Marketing Feature 9	5 Year Warranty