



DRV350700TD

20W CC Driver, Triac Mains Dimmable 350-700mA

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	130g
Inrush Current	15A 0.09ms
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	2
Case Temperature (tc = °C)	90
DIN Rail Mount	No
Install Connector Type	Push-fit terminals 0,5 - 1,5mm ²
Connection Output	Push-fit terminals
UK Protection	Open Circuit, Short Circuit, Over Temperature Self Reset
Power Factor	0.95

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
20W	350-700mA	220-240VAC	350-700mA	350mA: 9-40V - 500mA: 9-40V - 700mA: 9-29V	0.95



collingwood



TRIAC Dimmable



Quick and easy installation



IP20 Perfect for indoor applications

Guarantee

Warranty 5 years

Features & benefits

- Selectable drive currents through dip switches
- 350mA, 500mA and 700mA Selectable Settings
- The ability to select 3 lumen levels and use a dimmer
- Driver to power Residential Landscape luminaires

