



GU10 COMPACT FIRE RATED DOWNLIGHTS

EN-FD101

ENLITE GU10 **Fixed** Lock Ring Aluminium Fire Rated Downlight

EN-FD102

ENLITE GU10 **Adjustable** Lock Ring Aluminium Fire Rated Downlight

EN-FD103

ENLITE GU10 **IP65** Aluminium Fire Rated Downlight



FEATURES

- Loop-in/loop-out terminal block
- Twist and lock lamp retaining ring
- Integrated intumescent material completely seals the downlight and cut-out in the event of a fire
- Lamp not included
- Registered Community Design 915509-0001/2/3
- Tested in 30, 60 & 90 minute fire rated ceilings - BS476 Part 21
- Tested to BS EN ISO 140-3:1995 & BS EN ISO 140-6:1998 (Acoustics) confirming that they maintain the ability for an internal or separating floor to provide sound insulation
- **1 year guarantee**

Cat.No.	Max [W]	Input	Overall [Ø]	Cutout [Ø]	Recess	Horz. Adj.
FIXED						
EN-FD101W	50W	240V	87mm	75mm	110mm	-
EN-FD101PC	50W	240V	87mm	75mm	110mm	-
EN-FD101SN	50W	240V	87mm	75mm	110mm	-
ADJUSTABLE						
EN-FD102W	50W	240V	100mm	90mm	115mm	28°
EN-FD102PC	50W	240V	100mm	90mm	115mm	28°
EN-FD102SN	50W	240V	100mm	90mm	115mm	28°
IP RATED						
EN-FD103W	50W	240V	86mm	75mm	130mm	-
EN-FD103PC	50W	240V	86mm	75mm	130mm	-
EN-FD103SN	50W	240V	86mm	75mm	130mm	-

Finish Options:

