

**GUARANTEE / WARRANTY**

7 year extended warranty

**FEATURES & BENEFITS**

A stylish, baffled mini ground light

Perfect for both interior and exterior applications

Compliments environments with ultra low glare up-lighting effect

Can also be powered by a 700mA low voltage driver if more light is needed

A sleek black finish

# GL019 Ultra low-glare

1W, 78lm mini ground light

**FEATURES**

|                        |                 |
|------------------------|-----------------|
| IP rating              | IP68            |
| Colour flexibility     | Fixed colour    |
| Walk Over / Drive Over | No              |
| Input                  | 350mA / 700mA   |
| LED Lifetime           | 70,000h L70 B10 |
| CRI                    | >80Ra           |
| SDCM                   | 3SDCM           |

**INSTALLATION INFORMATION**

|                             |                    |
|-----------------------------|--------------------|
| Cut Out Size                | Ø 33mm             |
| Bathroom zone               | 0                  |
| Efficiency                  | DRIVER DEPENDANT   |
| Construction Material       | Anodised aluminium |
| Weight                      | 141g               |
| Maximum ambient temperature | 50°C               |
| Electric Class (1, 2, 3)    | 3                  |

**PHOTOMETRICS @ 25°C**

| Product code | Wattage               | Colour | Beam angle | lm | lm/W | lx @ 1m |
|--------------|-----------------------|--------|------------|----|------|---------|
| GL019BMBL27  | 1W (350mA) 2W (700mA) | 2700K  | 30°        | 60 | 60   | 24      |
| GL019BMBL30  | 1W (350mA) 2W (700mA) | 3000K  | 30°        | 64 | 64   | 25      |
| GL019BMBL40  | 1W (350mA) 2W (700mA) | 4000K  | 30°        | 68 | 68   | 125     |
| GL019BNBL27  | 1W (350mA) 2W (700mA) | 2700K  | 12°        | 70 | 70   | 1292    |
| GL019BNBL30  | 1W (350mA) 2W (700mA) | 3000K  | 12°        | 74 | 74   | 1324    |
| GL019BNBL40  | 1W (350mA) 2W (700mA) | 4000K  | 12°        | 78 | 78   | 2369    |

**WIRING INFORMATION**

|                         |   |
|-------------------------|---|
| Cable / Flying Lead     | 1m (H05RN-F) rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series  |

# GROUND LIGHTS SPECIFICATION SHEET

---

## LED DRIVERS

| Product code        | Input    | SELV | Dimming     | Bathroom zone | Min | Max |
|---------------------|----------|------|-------------|---------------|-----|-----|
| PLU/350 1-9         | 220-240V | Yes  | No          | 1             | 1   | 9   |
| PLR/350 1-5         | N/A      | Yes  | No          | 0             | 1   | 5   |
| PLD UNI-DRIVE 350MA | N/A      | Yes  | Yes (1-10V) | 2             | 1   | 10  |

---


## ACCESSORIES


No accessories required




**COLLINGWOOD**  
LIGHTING

01604 495 151  
[collingwoodlighting.com](http://collingwoodlighting.com)

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

---

## GL019 Ultra low-glare

This ultra low-glare, IP68 ground light is a stunning product for illuminating entrance halls, pathways and circulation areas of both interiors and exteriors. The light source is recessed further back into the ground keeping it hidden from view, but still provides a powerful upwards light beam. This sleek black finish will give a flawless performance for many years of maintenance-free operation. Available in three colour temperatures, two finishes and two beam angles, this product will suit any interior or exterior design.