

Technical Specification

Product Code: GM2008GTBK

Description: 250V~ Illuminated Blank Module



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 19.5 (D)		
Finish	Black		
Insert Colour	Green LED		
Materials	Transparent Trim: Polycarbonate Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated	Blank Section: Polycarbonate Terminals: Brass	
Anti Microbial Certified	No		
Rated Voltage (V~) (Ue)	250	Frequency (Hz)	50
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm²)	3 x 2.5, 2 x 4		
LED Indicator	Yes	Indicator Colour	Green
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10	Warranty - Electronics (Years)	1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Bespoke laser etching is available on request.

UK Patent: GB 2578427

