

**Technical Specification**

**Product Code:** GM2515BK

**Description:** 2.4A Type A USB Charging Module



**General Information**

<b>Dimensions (mm)</b>	24.5 (W) x 50 (H) x 40 (D)	
<b>Finish</b>	Black	
<b>Materials</b>	Front Covers: Nylon	Rear Housing: Nylon
	Electronics: USB Connections & Cable	Fixing Screws: Nickel Plated Steel
<b>Anti Microbial Certified</b>	No	
<b>Rated Voltage (V~) (Ue)</b>	240	<b>Frequency (Hz)</b> 50/60
<b>Resistive Load Rating (A)</b>	2.4	
<b>USB Output Type</b>	USB Type "A"	
<b>USB Number Of Outputs</b>	1	<b>USB Charging Total Load (A)</b> 2.4
<b>USB Charging Voltage (V DC)</b>	5	<b>USB Standby Current (mA)</b> 1
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	5 x 5	<b>Terminal Torque Value (Nm)</b> 1.2
<b>Terminal Capacity - Solid (mm²)</b>	3 x 2.5, 2 x 4 or 1 x 6.0	
<b>Product Marking</b>	Charging USB Icon + 5V DC 2.4A	
<b>Minimum Back Box Depth (mm)</b>	35 (47 Flat Plate)	
<b>Ingress Protection</b>	IP20	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	2	

**Additional Information** For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Internally fused which enables direct mains supply.