

## SL Recessed Ceiling Fan Heaters - Wireless Controlled

Designed to fit in place of a 600mm standard ceiling panel. This makes it ideal to heat areas where wall and floor space is at a premium such as shops and offices.

- 3kW, 4.5kW or 6kW rating
- Wireless controlled by separately purchased SL or CRXSL controller
- One SL or CRXSL controller can operate multiple SL heaters
- Choice of controllers:
  - SLPB: Run-back timer and thermostat
  - SLVT: Run-back timer and adjustable thermostat
  - SLVTB: Battery-powered run-back timer and adjustable thermostat
  - CRXSL: Programmable 7-day timer and thermostat
- Fits standard 600mm modular suspended ceiling system
- Sealed heater box for improved energy efficiency
- Will fit shallow 210mm recess
- Light weight for easy installation
- Quiet operation
- Automatic safety cut-out
- LED indicator light
- Complete with white aluminium diffuser



Model No.	Rating (kW)	Optimum Ceiling Height (m)	dBA
HE7230SL	3	3.0	37
HE7245SL	4.5	3.3	38
HE7260SL	6	3.6	40

### Dimensions (mm) & Weight (kg):

Rating (kW)	Depth	Width	Length	Weight
3, 4.5	175	595	595	7.5
6	175	595	595	10.5