

RX Surface Mounted Air Curtains - Wireless Controlled

A welcoming curtain of warmth in shops, hotels, offices and other commercial premises with the added benefit of energy saving and comfort control.

- 3kW, 4.5kW and 6kW models
- 634mm and 1040mm widths
- Wall mounting bracket supplied for ease of installation and angular adjustment
- Suspended, wall or trunking mounted
- Wireless controlled by a separately purchased RX controller
- Choice of RX heating system:
 - Single-zone with CRXSL
 - Multizone with MRX1 and CRXSL
 - RXLC landlord control with MRXLC and CRXLC
- CRXSL and CRXLC controllers can operate multiple RX heaters
- Fan only setting for air circulation
- Automatic safety cut-out for thermal overload protection
- Finished in white



Dimensions (mm) & Weight (kg):

Model No.	Height	Depth	Width	Weight
HE7402RX/HE7420RX	210	115	634	5.1
HE8320RX/HE7426RX	210	115	1040	8.8

Note: Only 200mm clearance from ceiling required.

Model No.	Rating (kW)	Max Mounting Height (m)	dBA
HE7402RX	3	2.3	46
HE7420RX	4.5	2.3	46
HE8320RX	4.5	2.3	49
HE7426RX	6	2.3	49