

HT IP66

Steel enclosures used to house electrical or electronic switchgear, control gear and equipment.

Mainly used for industrial electrical installations as enclosures for measurement, transmission, signposting and control equipment or as enclosures for all the equipment necessary to co-ordinate the different electrical currents.

The design and manufacture of this product line is sufficiently flexible so as to adapt to special executions that require specific dimensions in agreement with user and installation requirements.

Manufactured from high quality materials in cold-rolled plate of up to 2mm thick and coated with RAL7035 hardened epoxy polyester paint.



- Degree of protection is IP66
- Resistance to impact is IK10
- Range of temperature under normal conditions
-25°C/+40°C
- Maximum operation voltage (Ue) 1000V
- RAL7035 epoxy-polyester paint*
- Range of accessories available

*** Comes complete with Mounting Plate**

Steel Enclosures		Dimensions (mm)		
HT Product Code	Description	Height	Width	Depth
HT252015	IP66 Mild Steel Enclosure c/w mtg plate	250	200	150
HT302515	IP66 Mild Steel Enclosure c/w mtg plate	300	250	150
HT302520	IP66 Mild Steel Enclosure c/w mtg plate	300	250	200
HT303015	IP66 Mild Steel Enclosure c/w mtg plate	300	300	150
HT303020	IP66 Mild Steel Enclosure c/w mtg plate	300	300	200
HT403015	IP66 Mild Steel Enclosure c/w mtg plate	400	300	150
HT403020	IP66 Mild Steel Enclosure c/w mtg plate	400	300	200
HT404020	IP66 Mild Steel Enclosure c/w mtg plate	400	400	200
HT504015	IP66 Mild Steel Enclosure c/w mtg plate	500	400	150
HT504020	IP66 Mild Steel Enclosure c/w mtg plate	500	400	200
HT504025	IP66 Mild Steel Enclosure c/w mtg plate	500	400	250
HT505025	IP66 Mild Steel Enclosure c/w mtg plate	500	500	250
HT604015	IP66 Mild Steel Enclosure c/w mtg plate	600	400	150
HT604020	IP66 Mild Steel Enclosure c/w mtg plate	600	400	200
HT605020	IP66 Mild Steel Enclosure c/w mtg plate	600	500	200
HT605025	IP66 Mild Steel Enclosure c/w mtg plate	600	500	250
HT606020	IP66 Mild Steel Enclosure c/w mtg plate	600	600	200
HT606025	IP66 Mild Steel Enclosure c/w mtg plate	600	600	250
HT606030	IP66 Mild Steel Enclosure c/w mtg plate	600	600	300
HT705020	IP66 Mild Steel Enclosure c/w mtg plate	700	500	200
HT705025	IP66 Mild Steel Enclosure c/w mtg plate	700	500	250
HT806020	IP66 Mild Steel Enclosure c/w mtg plate	800	600	200
HT806025	IP66 Mild Steel Enclosure c/w mtg plate	800	600	250
HT806030	IP66 Mild Steel Enclosure c/w mtg plate	800	600	300
HT808030	IP66 Mild Steel Enclosure c/w mtg plate	800	800	300
HT1008030	IP66 Mild Steel Enclosure c/w mtg plate	1000	800	300
HT1206030	IP66 Mild Steel Enclosure c/w mtg plate	1200	600	300
HT1010300	IP66 Mild Steel Enclosure c/w mtg plate	1000	1000	300
HT12080300	IP66 Mild Steel Enclosure c/w mtg plate	1200	800	300
HT12080400	IP66 Mild Steel Enclosure c/w mtg plate	1200	800	400

Reference	Description
HTWB	Wall Mounting Brackets
HTFOK	Fully Operated Key Lock
HTTL	8mm Triangular Lock
* S4002	Standard Replacement Double Bar Lock
* S1180	Wing Lock

Accessories available:

- Wall Brackets
- Locks



* other accessories available on request