

Handyflow Oversink

A

Vented Point of Use
Water Heater
5 litre



p66

Usage



Ideal for occasional use light dish washing at a single kitchen sink in the workplace, for example portable buildings, offices, shops, workshops, garages and other small commercial premises.

Features and Benefits

- Open outlet heater to supply hot water to a single sink
- Ideal when economy and ease of installation are the key priorities
- Stylish design and slimline profile – depth only 7" (180mm)
- Comes complete with tap and chrome spout
- Thermal cut-out can be re-set rather than requiring to be replaced
- 2.0 kW element
- External temperature control with frost protection setting
- Neon element on indicator
- Wall fixing bracket included and cable pre-wired (1m) – saves time on installation
- No need for expansion vessel, relief valve or reducing valve

Product Code	Capacity (litres)	Power (kW)	Heat Up Time (mins)*	Standing Loss (kWh/day)
HFO5LM	5	2.0	12	0.32

*Heat up time from 10°C to 75°C



Outer Casing
Easy clean, high impact plastic

Heating Element
Incoloy-sheathed coil

Thermostat
Capillary type adjustable
to approx. 80°C
E setting approx. 55°C

Water Tank
Polypropylene

Insulation
High density polystyrene
CFC free

Spout
Length 10" (250mm)

Safety
Open outlet non-pressurised
system, supplied tap and spout
must be used.

Safety re-settable thermal cut out.
Frost protection setting when
power is switched on.

Heating Cycle
It is normal for the spout on this
type of unit to drip slightly during
the heating cycle, caused by the
water expanding as it heats up.

IP Rating
IP24

Installation
Must be sited above a sink using
the wall fixing bracket supplied,
with the spout and tap located
at the bottom of the unit.

Plumbing
Must be installed by a suitably
qualified person.

Minimum water pressure 0.3 bar.
Maximum water pressure 8 bar.

Water Connection
Inlet valve/ tap 1 x 15mm
compression.
Outlet 1 x chrome plated brass
spray arm.

**ONLY USE THE FITTINGS
SUPPLIED SO THAT THE UNIT
IS NOT PRESSURISED.**

Electrical Connection
Installation must comply
with current IEE regulations.

The product should be connected
to the fixed wiring of the property
via a double pole fused spur
with a minimum break capacity
of 13 amps.

Cable pre-wired (1m).

Approvals
CE

Standard Warranty
1 year parts or replacement
warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
HFO5LM	400	270	180	3.5	8.2