

## H07RN-F

Heavy standard construction

H07RN-F, HAR, power and control cable, rubber, heavy, 450/750 V, industrial and agricultural use, class 5, -25 °C to +60 °C, oil-resistant, flame-retardant

### Info

Medium mechanical stress

Oil-resistant



UV-resistant



Oil-resistant



Mechanical resistance



Cold-resistant



### Benefits

For mechanically more demanding applications

1000 V AC at protected + static laying

Arrangements made of single-core, rubber-sheathed cables H07RN-F can be used for short circuit-proof and short-to-ground-proof installations in accordance with IEC 60364-5-52/ HD 60364-5-52/ VDE 0100 Part 520

## H07RN-F

### Application range

Handheld and power supply devices according to EN 50565-2  
Medium, mechanical stress  
Industrial, agricultural use  
According to EN 50565-2: In dry, damp and wet rooms as well as for fixed installation e.g. on the plaster

### Product features

Flame-retardant according IEC 60332-1-2  
Oil-resistant according to EN 60811-404

### Norm references / Approvals

<HAR> H07RN-F cable type approval according to EN 50525-2-21

### Product Make-up

Bare copper wire according to HAR  
Core insulation: rubber compound, type EI 4  
Outer sheath: rubber compound, type EM2

### Technical Data

Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Core identification code:	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	4 to 8 x outer diameter (EN 50565-1)
Nominal voltage:	U0/U: 450/750 V
Test voltage:	2500 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Current rating:	According to IEC 60364-5-52/ VDE 0298-4 EN 50565-1/ VDE 0298-565-1
Temperature range:	-25°C to +60°C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil  $\leq$  30 kg or  $\leq$  250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**H07RN-F**

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1600096	1 X 1.5	5.7 - 7.1	14.4	59
1600099	1 X 2.5	6.3 - 7.9	24	72
1600097	1 X 4	7.2 - 9	38.4	99
1600098	1 X 6	7.9 - 9.8	57.6	130
1600194	1 X 10	9.5 - 11.9	96	230
1600195	1 X 16	10.8 - 13.4	153.6	320
1600196	1 X 25	12.7 - 15.8	240	450
1600193	1 X 35	14.3 - 17.9	336	605
1600197	1 X 50	16.5 - 20.6	480	825
1600189	1 X 70	18.6 - 23.3	672	1090
1600190	1 X 95	20.8 - 26	912	1405
1600198	1 X 120	22.8 - 28.6	1152	1745
1600191	1 X 150	25.2 - 31.4	1440	1887
1600175	1 X 185	27.6 - 34.4	1776	2274
1600177	1 X 240	30.6 - 38.3	2304	2955
30015435	1 X 300	33.5 - 41.9	2880	3479
1600117	3 G 1	8.3 - 10.7	28.8	130
1600199	2 X 1.5	8.5 - 11	28.8	135
1600103	3 G 1.5	9.2 - 11.9	43.2	165
16001233	4 G 1.5	10.2 - 13.1	57.6	200
16001043	5 G 1.5	11.2 - 14.4	72	240
1600151	7 G 1.5	14.7 - 18.7	100.8	385
1600148	12 G 1.5	17.6 - 22.4	172.8	516
1600259	19 G 1.5	20.7 - 26.3	273.6	800
1600166	24 G 1.5	24.3 - 30.7	345.6	882
1600263	25 G 1.5	25.1 - 25.9	360	920
1600187	2 X 2.5	10.2 - 13.1	48	195
1600118	3 G 2.5	10.9 - 14	72	235
16001053	4 G 2.5	12.1 - 15.5	96	290
16001293	5 G 2.5	13.3 - 17	120	294
1600152	7 G 2.5	17.1 - 21.8	168	520
1600154	12 G 2.5	20.6 - 26.2	288	810
1600156	19 G 2.5	25.5 - 31	456	1200
1600157	24 G 2.5	28.8 - 36.4	576	1650

Last Update (16.08.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet:  
PN 0456 / 02\_03\_16

**H07RN-F**

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1600186	2 X 4	11.8 - 15.1	76.8	270
1600119	3 G 4	12.7 - 16.2	115.2	320
16001063	4 G 4	14 - 17.9	153.6	395
16001303	5 G 4	15.6 - 19.9	192	485
1600161	7 G 4	20.1 - 25.5	268.8	681
1600120	3 G 6	14.1 - 18	172.8	360
16001073	4 G 6	15.7 - 20	230.4	475
16001313	5 G 6	17.5 - 22.2	288	760
1600121	3 G 10	19.1 - 24.2	288	880
16001083	4 G 10	20.9 - 26.5	384	1060
16001093	5 G 10	22.9 - 29.1	480	1300
1600122	3 G 16	21.8 - 27.6	460.8	1090
16001103	4 G 16	23.8 - 30.1	614.4	1345
16001113	5 G 16	26.4 - 33.3	768	1680
16001123	4 G 25	28.9 - 36.6	960	1995
16001133	5 G 25	32 - 40.4	1200	2470
1600124	3 G 35	29.3 - 37.1	1008	1910
16001143	4 G 35	32.5 - 41.4	1344	2645
16001363	5 G 35	35.7 - 45.1	1680	2810
16001153	4 G 50	37.7 - 47.5	1920	3635
1600126	5 G 50	41.8 - 53	2400	4050
16001163	4 G 70	42.7 - 54	2688	4830
16001283	4 G 95	48.4 - 61	3648	6320
16001323	4 G 120	53 - 66	4608	6830
16000883	4 G 150	58 - 73	5760	8320
1600141	4 G 185	64 - 80	7104	9800
1600183	4 G 240	72 - 91	9216	12800

Last Update (16.08.2017)

©2017 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)You can find the current technical data in the corresponding data sheet:  
PN 0456 / 02\_03\_16