

JC50322

3W Exit box self-test PC Housing/Acrylic c/w down legend IP20



General Information

| Product Group | Emergency |
|------------------------------|-------------------------------------|
| Product Range | Exit box |
| Range Name | self-test |
| Product Weight | 0.96kg |
| Finishes Available | White |
| Overall Dimensions | 390 x 190 x 27.5 mm |
| Recommended Product Location | Wall mount, indoor use only |
| Method Of Fix | Screws and rawl plugs(not supplied) |
| Ingress Protection (IP) | IP20 |
| Suitable For Zones | Outside zone 2 |

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

| Luminaire Accessories | JC50329(left/right/Up) legend pack |
|-----------------------|--------------------------------------|
| Origin Of Manufacture | Made in China |
| Guarantee | 3 years(2 years on batteries) |
| Operation Type | Maintained or non-maintained options |
| Mounting Height | Max 3 metres |
| Driver Manufacturer | JCC |
| LED Manufacturer/Type | Everlite 2835 |

Electrical

| Input Voltage (V) | 220-240V~ |
|------------------------------|---|
| Primary Running Current | 0.023-0.025A |
| Operating Frequency (Hz) | 50/60Hz |
| CC or CV | Constant current |
| Luminaire Circuit Wattage | 3W(AC)8.6W(DC) |
| Class | Class I, earth required |
| Input Electrical Connections | S/L(brown),U/S live(black),Neutral(blue), Earth(yellow/green) |
| Dimmable | No |

Emergency Data

| Load Voltage | 12V |
|--------------------------------|--------------------|
| Nominal Battery Current | 1200mAh |
| Recharge Time | 24hrs |
| Battery Specification | 3.6V,1200mAh Ni Cd |
| Battery Life In Emergency Mode | 3hrs |
| Charge Current | 73~85mA |
| DDP Protection | Yes |

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

| LOR In Emergency Mode | 100% |
|-----------------------|------|
| Inverter PFC | 0.65 |

Thermals

| Room Ambient Temperature Not To Exceed | 30°C |
|--|------|
| Room Ambient Temperature | 26°C |
| Max Luminaire Ambient Temp. | 25°C |

Performance Data

| Energy Rating | A |
|----------------------------|--------------------------------------|
| Lumen Output | 15 lumens(AC) 16 lumens(DC) |
| Lumens Per Circuit Watt | 5 Lpcw(AC) 5 LpcW(DC) |
| LED Life (Hours) | 50000 |
| CRI: Ra | 80 |
| Colour Temperature (K) | 6000K |
| LOR (Light Output Ratio) % | 100% |
| Photometry Available | yes |
| Detection Distance | Visible from a distance of 24 metres |

Construction

| Main Chassis | Polycarbonate |
|--------------|---------------|
| Diffuser | Acrylic |

Packaging

| Luminaire Carton Dimensions | 398 x 38 x 195 mm |
|-----------------------------|-------------------|
| Quantity Per Outer Carton | 10 |
| Bar Code EAN Number | 5052544080579 |

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

| Packaged Weight 1 | L.0kg |
|-------------------|-------|
|-------------------|-------|

Standards & Approvals

| Manufactured In Accordance To | BS EN60598-2-22 |
|-------------------------------|----------------------------------|
| CE Marked | yes |
| Batch Coded | yes |
| WEEE Symbol | yes |
| Certificate Of Conformity | Available on request |
| Accredited Members | LIA, ISO9001:2015, ISO14001:2015 |

Datasheet generated from http://www.electrika.cloud on 12 February 2018 07:47:00