

JC50326

Recessed Exit Blade Maintained 3M IP20 without legend

General Information

Product Group	Emergency
Product Range	Exit Blade
Range Name	Recessed
Product Weight	1.16kg
Finishes Available	White
Overall Dimensions	225 x 375 x 76 mm
Recommended Product Location	Recessed ceiling mount, indoor use only
Method Of Fix	Spring clips
Cut Out Ø	320 x 55 mm
Ingress Protection (IP)	IP20
Suitable For Zones	Outside zone 2
Luminaire Accessories	JC50308(left+right legend pack)JC50310(2 x down legend pack)JC50311(2 x Up legend pack)
Origin Of Manufacture	Made in China
Guarantee	3 years(2 years on batteries)
Operation Type	Maintained only
Mounting Height	Max 3 metres
Driver Manufacturer	JCC
LED Manufacturer/Type	Everlite 2835

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Electrical

Input Voltage (V)	220-240V~
Primary Running Current	0.015-0.019A
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant current
Luminaire Circuit Wattage	3W(AC)8.6W(DC)
Class	Class II, no earth required
Input Electrical Connections	U/S live(brown or black),Neutral(blue)
Dimmable	No

Emergency Data

Load Voltage	12V
Nominal Battery Current	900mAh
Recharge Time	24hrs
Battery Specification	3.6V,900mAh Ni Cd
Battery Life In Emergency Mode	3hrs
Charge Current	59-132mA
DDP Protection	Yes
LOR in Emergency Mode	100%
Inverter PFC	0.58

Thermals

Room Ambient Temperature Not To Exceed	30°C
Room Ambient Temperature	26°C
Max Luminaire Ambient Temp.	25°C

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Performance Data

Energy Rating	A
Lumen Output	40 lumens(AC) 40 lumens(DC)
Lumens Per Circuit Watt	13 Lpcw(AC) 13 LpcW(DC)
LED Life (Hours)	50000
CRI: Ra	87
Colour Temperature (K)	6000K
LOR (Light Output Ratio) %	100%
Photometry Available	yes
Detection Distance	Visible from a distance of 24 metres

Construction

Main Chassis	Polycarbonate
Diffuser	Acrylic

Packaging

Luminaire Carton Dimensions	345 x 85 x 218 mm
Quantity Per Outer Carton	10
Bar Code EAN Number	5052544080616
Packaged Weight	1.21kg

Standards & Approvals

Manufactured In Accordance To	BS EN60598-2-22
CE Marked	yes
Batch Coded	yes
WEEE Symbol	yes

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

Datasheet generated from http://www.electrika.cloud on 12 February 2018 08:35:17