

Zen Life 100°C

Boiling Water Tap with Kitchen Hot and Cold Mixer 3 and 6 litre boiling water tank



Usage

The Zen Life is a practical and stylish choice when considering the design and requirements of any kitchen environment. The elegant 3 in 1 tap provides instant true boiling 100°C water alongside hot and cold mixer tap capabilities.



It is perfect for retro-fit applications as well as new kitchens. This is the only tap you need in your kitchen and is ideal for a range of domestic and commercial applications.

Features and Benefits

- Creates a clutter free and simplified design within any kitchen or office
- Instant true boiling 100°C water ideal for a wide range of kitchen uses
- Designed and assembled in the UK
- Time and space saving
- Energy efficient - costs just 4 p a day, based on standing losses 17 W. Electricity cost 10 p/ kWh.
- Safety lock on the boiling water side
- Innovative aerogel insulation on boiling water tank minimises losses
- Boiling water tank has smart technology algorithms that learn and predict usage
- Cool touch insulated tap with 360° swivel function
- Zen Life tap should be mounted over a sink. Not suitable for use with a Zen font and drain.
- Boiling water status ring on base of tap to indicate ready or heating (green/ red LED)
- Available in 3 or 6L. 6L model comprises 2 x 3 litre boiling water tanks with linking kit.
- Power rating 1.55 kW for 3 litre model and 2 x 1.55 kW for 6 litre model
- Standard sink hot and cold mixer supplied from your existing hot and mains cold water supply
- Consider installing a Speedflow to provide hot water for dish washing if there is no central heating system nearby
- If you are in a hard scale area you may need a scale filter on the inlet side of the boiling tank F5SST or F4SST depending on degree of scale (page 38)
- Elongated mixer lever for ease of use
total length 100 mm
length from centre 80 mm
- Shorter mixer lever for restricted space kitchens total length 70 mm length from centre 55 mm
- Recovery Rate
100 cups/ 70 mugs per hour based on 167 ml cup and 250 ml mug
- Double recovery rate for 6 litre model

Product Code	Capacity (litres)	Heat Up Time (mins)	Standing Loss (kWh/day)*
LIFE3L	3	13	0.42 17 W
LIFE6L	6	13	0.84 34 W

* The 6 litre model comprises 2 x 3L tanks. Costs 8 p a day for 2 x 3L tanks.



Outer Casing

Tap – polished chrome finish as standard
Other tap finishes available at additional cost (page 13)
Tank – durable high impact PC/ ABS

Water Tank

High quality grade 316L stainless steel

Heating Element

Incoloy

Thermostat

Electronic to control water up to boiling point

Insulation

Highly efficient aerogel thermal insulation

Initial Draw off

16 cups/ 11 mugs based on 167 ml cup and 250 ml mug.
Double draw off for 6 litre model.

Safety

Overheat temperature protection (manual re-set).

Safety lock mechanism.

Supplied expansion vessel and pressure relief valve must be fitted.

IP Rating

IPX1

Installation

This appliance must be installed

in a frost free environment

Required hole diameter for mounting tap 32mm – fits in a standard sink.
Sink/ counter top up to 50mm thick.

The dispensed water temperature can be adjusted down to 98°C on installation if required.

Plumbing

Must be installed by a suitably qualified person.

Intended for connection to the mains water supply.

Minimum water pressure 1 bar.

Maximum water pressure 4.2 bar. If higher than this a pressure reducing valve may be required.

Supplied expansion vessel and pressure relief valve must be fitted.

Electrical Connection

Installation must comply with current IEE wiring regulations.

Supplied with a pre-wired (1m) BS plug.

Approvals

CE

Standard Warranty

2 years parts or replacement warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
ZEN Life Tap (all models)	365	286	56	2.5	–
ZEN Life 3L Tank	459	181	220	5.8	8.8