

# Technical Specification

**Product Code:** MD023AB

**Description:** 20A Ingot Double Pole Switch With Neon Module



## General Information

<b>Dimensions (mm)</b>	41 (W) x 52.5 (H) x 22 (D)	
<b>Finish</b>	Antique Brass	
<b>Materials</b>	Rocker Switch: Urea Switch Cover: Stainless Steel Terminals: Brass Contacts: Silver "on-lay" Copper / Brass	Rear Housing: Nylon Neon Cover: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Resistive Load Rating (A)</b>	20	
<b>Termination Type</b>	Screw	<b>Terminal Torque Value (Nm)</b> 1.2
<b>Terminal Size (mm)</b>	Ø4.4	
<b>Terminal Capacity - Solid (mm²)</b>	3 x 2.5 or 2 x 4	
<b>Modular Rocker Switches</b>	Yes	
<b>Double Pole Switch</b>	Yes	
<b>Neon Indicator</b>	Yes	<b>Indicator Colour</b> Red
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	

**Standards** BS EN 60669-1: 2018

**Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.