

## **Technical Specification**



L COM

## Product Code: MD024BN

Description: 20A Ingot 2 Way Switch Module

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.			
Standards	BS EN 6	60669-1: 2018	
Warranty (Years)		10	
Operational Temperature (°C)		-5 to +40	
Minimum Back Box Depth (mm)		25 (35 Flat Plate)	
2 Way Switch		Yes	
Modular Rocker Switches		Yes	
Terminal Capacity - Solid (mm <sup>2</sup> )		3 x 2.5 or 2 x 4	
Terminal Size (mm)			al Torque Value (Nm) 1.2
Resistive Load Rating (A) Termination Type		20 Screw	
Rated Voltage (V~) (Ue)		250 20	Frequency (Hz) 50
		Internal Busbars: Formed Pressed Brass	<b>F</b> (11) FO
		Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
		Switch Cover: Stainless Steel	Terminals: Brass
Materials		Rocker Switch: Urea	Rear Housing: Nylon
Finish		Black Nickel	
Dimension	s (mm)	41 (W) x 52.5 (H) x 22 (D)	
General Inforn	nation		
			20A 250V~ BSEN 60669 CLICK 024 L2 024 L1

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com



Page 1 of 1 (01/11/21) Errors & Omissions excluded. Specification is subject to change without notice.