

Product Code: MD028AB

Description: 10AX Ingot Intermediate Switch Module



General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)	
Finish	Antique Brass	
Materials	Rocker Switch: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Rear Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
Intermediate Switch	Yes	
Minimum Back Box Depth (mm)	16 (25 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.