

Technical Specification

Product Code: MD070AB

Description: 10A Ingot 3 Position Switch Module



General Information

| | | |
|--|--|---|
| Dimensions (mm) | 25 (W) x 57 (H) x 27 (D) | |
| Finish | Antique Brass | |
| Materials | Rocker Switch: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass | Rear Housing: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 10 | Terminal Torque Value (Nm) 0.5 |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 2 x 2.5 | |
| Modular Rocker Switches | Yes | |
| 1 Pole 3 Position Switch | Yes | |
| Minimum Back Box Depth (mm) | 25 (35 Flat Plate) | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |
| Standards | BS EN 60669-1: 2018 | |

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.