

ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV

0.6/1kVAC, Halogen-free, Flexible, IEC 60332-3, IEC 61034-2, UV/ ozone resistance, UL AWM 1000V


ÖLFLEX® CLASSIC 135 CH BK 0,6/1kV: Power and Control Cable UL AWM Style 21156 Class 5, Screened, Halogen-free/ Highly Flame Retardant, Public buildings, Outdoor

Info

Outdoors

Public buildings

EMC/Screened



UV-resistant



Interference signals



Halogen-free



Suitable for outdoor use



Flame-retardant



Cold-resistant

Benefits

Easy installation due to flexible design

Space-saving installation due to small cable diameters

Last Update (13.09.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV

Application range

Public buildings
Plant engineering
Industrial machinery
Heating and air-conditioning systems
Particularly where human and animal life as well as valuable property are exposed to high risk of fire hazards
For outdoor applications
According to NFPA 79, 2015 Edition, subchapter 12.9.2: Use for industrial machinery operated in the USA on the basis of UL AWM (recognized) certification

Product features

Flame-retardant according to IEC 60332-1-2
(flame spread on a single cable)
No flame-propagation according to IEC 60332-3-24 respectively IEC 60332-3-25 (Flame spread on vertical cable or wire bundle)
Halogen-free according to IEC 60754-1
(amount of halogen acid gas)
Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)
Low smoke density according to IEC 61034-2
UV and weather-resistant according to ISO 4892-2
Ozone-resistant according to EN 50396
UL Cable Flame Test

Norm references / Approvals

Based on EN 50525-3-11
UL AWM (recognized) Style 21156 (outer jacket) with max. conductor temperature of +75 °C acc. to UL

Product Make-up

Fine-wire strand made of bare copper wires
Core insulation: Halogen-free
Halogen-free plastic foil wrapping
Tinned-copper braiding
Outer sheath made of special halogen-free compound, black (RAL 9005)

ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000057 ETIM 5.0 Class-Description: Low voltage power cable
Core identification code:	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter
Nominal voltage:	U0/U: 600/1000 V UL: 1000 V
Test voltage:	Core/core: 4000 V Core/screen: 2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -25 °C to +70 °C Fixed installation: -40 °C to +80 °C UL: +75 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**LAPP GROUP**

PRODUCT INFORMATION

ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV

Article number	Number of cores and mm² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1123460	2 X 1	9.4	39.5	120
1123461	3 G 1	9.8	51	140
1123462	4 G 1	10.4	62.8	165
1123463	5 G 1	11.2	76	191
1123464	7 G 1	11.9	97.2	231
1123465	12 G 1	15	169.1	360
1123466	18 G 1	17.3	238.2	494
1123467	25 G 1	19.8	315.5	643
1123468	2 X 1.5	10.4	53.2	149
1123469	3 G 1.5	10.9	69.5	177
1123470	4 G 1.5	11.6	86.5	209
1123471	5 G 1.5	12.5	104.3	243
1123472	7 G 1.5	13.4	136.5	300
1123473	12 G 1.5	17.3	238.3	486
1123474	18 G 1.5	20.2	355.4	691
1123475	25 G 1.5	23.1	475.1	914
1123476	2 X 2.5	11.6	79.4	197
1123477	3 G 2.5	12.1	106.1	243
1123478	4 G 2.5	13	134.3	293
1123479	5 G 2.5	14.1	158.3	342
1123480	7 G 2.5	15.4	225	462
1123481	12 G 2.5	20.1	383.6	718
1123482	18 G 2.5	23.4	548.9	1011
1123483	25 G 2.5	27.4	761.7	1370
1123485	4 G 4	14.7	211.9	399
1123486	5 G 4	15.9	250.3	471
1123487	3 G 6	14.9	232.1	414
1123488	4 G 6	16.1	298.5	519
1123489	5 G 6	17.8	356.1	607
1123490	4 G 10	20.1	490.6	837
1123492	4 G 16	22.5	735.1	1157
1123493	5 G 16	25	888.7	1407
1123494	4 G 25	27.8	1,126.6	1683

Last Update (13.09.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16