

# Omega

## Wall Mounted Boiling Water Heater 3 and 5 litre



p.40

### Usage



The Omega is a practical, stylish wall mounted unit that provides instant boiling water for preparing hot drinks in the workplace. The sleek, ergonomic design with curved lines gives a contemporary look whilst the robust, durable design specification makes it an essential appliance in a work environment.

### Features and Benefits

- Designed and assembled in the UK
- 2.85 kW gives fast heat up time and high recovery rate
- Time saving – provides instant hot water so no need to wait for the kettle to boil
- Space saving – frees up worktop space by eliminating the need for a kettle
- Energy efficient - costs just 5 p a day, based on standing losses 23 W. Electricity cost 10 p/ kWh.
- Status ring on base of control valve to indicate ready or heating (green/ red LED)
- Robust, heavy duty control valve
- Cool touch control valve and water outlet reduce heat losses
- Simple to use and easy to install
- Durable, high impact and easy to clean white ABS case
- Sophisticated electronics maintain a constant supply of hot water - even when the unit is automatically re-filling after heavy usage
- Autocalibration for optimal temperature
- 1 year on-site warranty as standard
- 3 year on-site warranty available on request at additional cost
- **It is highly recommended that a filter system is fitted to protect against scale build up. Units may need to be de-scaled regularly. Scale damage is not covered by the warranty (see page 38).**

Product Code	Capacity (litres)	Initial Draw Off (cups/ mugs)*	Heat Up Time (mins)	Standing Loss (kWh/day)
OMEG3	3	18/ 12	6	0.55 23 W
OMEG5	5	30/ 20	10	0.55 23 W

\*Initial draw off based on 167 ml cup and 250 ml mug



**Outer Casing**

Easy clean high impact  
Polycarbonate/ ABS

**Heating Element**

2.85 kW incoloy-sheathed  
type element

**Thermostat**

Electronic to control water  
up to boiling point

**Water Tank**

Stainless steel

**Insulation**

EPP (expanded polypropylene)

**Filter System**

Optional extra - highly  
recommended.

See page 38 for filter options.

**IP Rating**

IPX0

**Recovery Rate**

Recovery rate 175 cups per hour  
for all models based on 167 ml  
cup size.

**Installation**

Install over a draining board,  
or work top fitted with a drip tray.  
At least 110mm clearance must  
be left above and below the unit  
to allow later removal of the jacket  
for service.

**Plumbing**

Must be installed by a suitably  
qualified person.

Minimum water pressure 1 bar.

Maximum water pressure 10 bar.

**Water Connection**

Inlet/ Outlet 2 x 15mm  
compression.  
1 x tundish recommended.

**Electrical Connection**

Installation must comply  
with current IEE regulations.

The product should be connected  
to the fixed wiring of the property  
via a double pole fused spur  
with a minimum break capacity  
of 13 amps.

Cable pre-wired (1.5m),  
to the bottom left.

**Maintenance**

It is recommended the unit is  
descaled every 6 months.

Drain in base of unit facilitates  
de-scaling

**Approvals**

CE

**Standard Warranty**

1 year on-site warranty as standard.

3 year on-site warranty available at  
additional cost.

Product Code	Height (mm)	Width (mm)	Depth (mm)*	Weight (kg)	
				Empty	Full
OMEG3	500	330	255	7	10
OMEG5	500	330	255	7	12

\*Depth includes front control. Distance of water outlet from wall is 180mm.