

**MULTI-FIT PLUS DOWNLIGHT 65-205MM CUTOUT 950-1700lm 10W 15W 18W  
3000K 4000K 6500K NON-DIMM 100LM/W WHITE**

ILD205-65G009



The Multi-Fit Plus Downlight provides a solution for commercial and home use with the adaptability to provide a suitable fitting and a high-quality lumen and colour adjustable light to match your space. This downlight gives increased versatility with the options of 3 Colour Temperatures (CCT); Warm White, Cool White, and Daylight and a Variable Wattage (Light Output) giving a range of nine lumen outputs from 950lm to 1550lm (Switches are located on the rear of the unit). A configurable cut-out size from 65 to 205mm with a surface mount option provides installation flexibility. The integrated driver eliminates visible flicker, and a frosted diffuser delivers a uniform light.

**Details**

<b>Quick Order Code:</b>	381351
<b>Barcode:</b>	5055788253051
<b>Category:</b>	Downlights
<b>Range Name:</b>	Multi-Fit+
<b>Product Type:</b>	LED Downlights
<b>Product Body Finish:</b>	Matt white
<b>Market Segment:</b>	Commercial indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Depth (mm):</b>	22
<b>Product Weight (g):</b>	405
<b>Optic:</b>	TP(b) rated Opal diffuser
<b>Material:</b>	Aluminium, PS, PC
<b>Overall diameter (mm):</b>	230
<b>Construction:</b>	Die cast Aluminium body, PS sheet diffuser
<b>Cut Out Diameter (mm):</b>	65-205
<b>Luminaire Fixing:</b>	Recess or surface mounted
<b>Placement / Application:</b>	Indoor, General Lighting

**Electrical Data**

<b>Power Consumption (w):</b>	10 to 18
<b>Power Factor:</b>	0.5

<b>Wattage equivalent (W):</b>	26
<b>Dimming:</b>	Non-Dimmable
<b>Driver Included:</b>	Integrated
<b>Electric Current:</b>	AC
<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes

## Light Data

<b>Luminous Flux in Lumens (lm):</b>	950-1700
<b>Luminous efficacy (lm/W):</b>	83-110
<b>Correlated Colour Temperature (CCT) (K):</b>	300040006500
<b>Colour Temperature Name:</b>	Warm White - Cool White - Daylight
<b>Beam Angle:</b>	110
<b>Colour Rendering Index (CRI):</b>	80
<b>LED Type:</b>	Surface mounted device (SMD)
<b>Lifetime (hours):</b>	30000
<b>Switching Cycles:</b>	15000

## Environment

<b>EN:</b>	EN-60598
<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Hg 0% (Mercury Free):</b>	Yes
<b>IP Rating (Ingress Protection):</b>	IP20
<b>Lowest Operating Temperature (°C):</b>	-10
<b>Maximum Operating Temperature (°C):</b>	40

## Packaging