



Ring

Part Number	Stud Size	Pack Qty
QRR3	3mm	100
QRR37	3.7mm	100
QRR4	4mm	100
QRR5	5mm	100
QRR6	6mm	100
QRR8	8mm	100
QRR10	10mm	100
QRR12	12mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 13A Voltage (max): 600V



Male Push-on

Part Number	Tab Size mm	Pack Qty
QRPO28M5	2.8mm X 0.5mm	100
QRPO28M8	2.8mm X 0.8mm	100
QRPO48M5	4.8mm X 0.5mm	100
QRPO48M8	4.8mm X 0.8mm	100
QRPO63M	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Female Push-on

Part Number	Tab Size mm	Pack Qty
QRPO28F5	2.8mm X 0.5mm	100
QRPO28F8	2.8mm X 0.8mm	100
QRPO48F5	4.8mm X 0.5mm	100
QRPO48F8	4.8mm X 0.8mm	100
QRPO63F	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Spade

Part Number	Stud Size	Pack Qty
QRF3	3mm	100
QRF3N	3.5mm	100
QRF4N	4mm	100
QRF5	5mm	100
QRF6	6mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 19A Voltage (max): 600V



Female Push-on Fully Insulated

Part Number	Tab Size mm	Pack Qty
QRFPQ28F5	2.8mm X 0.5mm	100
QRFPQ28F8	2.8mm X 0.8mm	100
QRFPQ48F5	4.8mm X 0.5mm	100
QRFPQ48F8	4.8mm X 0.8mm	100
QRFPQ63F	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Blade

Part Number	Dia. x Length mm	Pack Qty
QRBL10	2.3mm X 10mm	100
QRBL14	2.3mm X 14mm	100
QRBL18	2.3mm X 18mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 15A Voltage (max): 600V



Butt

Part Number	Pack Qty
QRB	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Piggy Back Push-on Connector

Part Number	Tab Size mm	Pack Qty
QRPOA63	6.3mm X 0.8mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Pin

Part Number	Dia. x Length mm	Pack Qty
QRP12	1.9mm X 12mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 15A Voltage (max): 600V



Heat Shrink Butt

Part Number	Pack Qty
QHSB1	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 13A Voltage (max): 600V



Male Bullet

Part Number	Bullet Dia mm	Pack Qty
QRAB4M	4mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Female Bullet

Part Number	Bullet Dia mm	Pack Qty
QRAB4F	4mm	100

Cable size range: 0.5 - 1.5mm²
Current rating (max): 10A Voltage (max): 600V



Ring

Part Number	Stud Size	Pack Qty
QBR3	3mm	100
QBR37	3.7mm	100
QBR4	4mm	100
QBR5	5mm	100
QBR6	6mm	100
QBR8	8mm	100
QBR10	10mm	100
QBR12	12mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 24A Voltage (max): 600V



Male Push-on

Part Number	Tab Size mm	Pack Qty
QBPO48M5	4.8mm X 0.5mm	100
QBPO48M8	4.8mm X 0.8mm	100
QBPO63M	6.3mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Female Push-on

Part Number	Tab Size mm	Pack Qty
QBPO48F5	4.8mm X 0.5mm	100
QBPO48F8	4.8mm X 0.8mm	100
QBPO63F	6.3mm X 0.8mm	100
QBPO85F	8.5mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Spade

Part Number	Stud Size	Pack Qty
QBF3	3mm	100
QBF3N	3.5mm	100
QBF4N	4mm	100
QBF5	5mm	100
QBF6	6mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 24A Voltage (max): 600V



Female Push-on Fully Insulated

Part Number	Tab Size mm	Pack Qty
QBFPQ48F5	4.8mm X 0.5mm	100
QBFPQ48F8	4.8mm X 0.8mm	100
QBFPQ63F	6.3mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Blade

Part Number	Dia. x Length mm	Pack Qty
QBBL9	2.8mm X 9mm	100
QBBL18	2.2mm X 18mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 24A Voltage (max): 600V



Butt

Part Number	Pack Qty
QBB	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Piggy Back Push-on Connector

Part Number	Tab Size mm	Pack Qty
QBPOA63	6.3mm X 0.8mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Pin

Part Number	Dia. x Length mm	Pack Qty
QBP12	1.9mm X 12mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 27A Voltage (max): 600V



Heat Shrink Butt

Part Number	Pack Qty
QHSB2	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 27A Voltage (max): 600V



Male Bullet

Part Number	Bullet Dia mm	Pack Qty
QBAB4M	4mm	100
QBAB5M	5mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V



Female Bullet

Part Number	Bullet Dia mm	Pack Qty
QBAB4F	4mm	100
QBAB5F	5mm	100

Cable size range: 1.5 - 2.5mm²
Current rating (max): 15A Voltage (max): 600V

Ring



Part Number	Stud Size	Pack Qty
QYR4	4mm	100
QYR5	5mm	100
QYR6	6mm	100
QYR8	8mm	100
QYR10	10mm	100
QYR12	12mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 37A Voltage (max): 600V

Male Push-on



Part Number	Tab Size mm	Pack Qty
QYPO63M	6.3mm X 0.8mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Female Push-on



Part Number	Tab Size mm	Pack Qty
QYPO63F	6.3mm X 0.8mm	100
QYPO95F	9.4mm X 1.2mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Spade



Part Number	Stud Size	Pack Qty
QYF3N	3.5mm	100
QYF4N	4mm	100
QYF5	5mm	100
QYF6	6mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 37A Voltage (max): 600V

Female Push-on Fully Insulated



Part Number	Tab Size mm	Pack Qty
QYFPO63F	6.3mm X 0.8mm	100
QYFPO95F	9.4mm X 1.2mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Blade



Part Number	Dia x Length mm	Pack Qty
QYBL10	2.8mm X 10mm	100
QYBL18	4.5mm X 18mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 37A Voltage (max): 600V

Butt



Part Number	Pack Qty
QYB	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Piggy Back Push-on Connector



Part Number	Tab Size mm	Pack Qty
QYPOA63	6.3mm X 0.8mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Pin



Part Number	Dia x Length mm	Pack Qty
QYP14	2.9mm X 14mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 37A Voltage (max): 600V

Heat Shrink Butt



Part Number	Pack Qty
QHSB5	100

Cable size range: 2.5 - 4mm²
Current rating (max): 37A Voltage (max): 600V

Male Bullet



Part Number	Bullet Dia mm	Pack Qty
QYAB5M	5mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Female Bullet



Part Number	Bullet Dia mm	Pack Qty
QYAB5F	5mm	100

Cable size range: 2.5 - 4mm²
Current rating (max): 24A Voltage (max): 600V

Bootlace Ferrules

Part Number	Description	Cable Size	Ferrule Length	Ferrule Diameter	Colour	Pack Quantity
QBFR05	White Bootlace Ferrule Single 0.5mm	0.5mm ²	8mm	1.05mm	White	100
QBFR075	Blue Bootlace Ferrule Single 0.75mm	0.75mm ²	8mm	1.25mm	Blue	100
QBFR1	Red Bootlace Ferrule Single 1.0mm	1mm ²	8mm	1.45mm	Red	100
QBFR15	Black Bootlace Ferrule Single 1.5mm	1.5mm ²	8mm	1.8mm	Black	100
QBFR25	Grey Bootlace Ferrule Single 2.5mm	2.5mm ²	8mm	2.3mm	Grey	100
QBFR4	Orange Bootlace Ferrule Single 4mm	4mm ²	10mm	2.9mm	Orange	100
QBFR6	Green Bootlace Ferrule Single 6.0mm	6mm ²	12mm	3.6mm	Green	100
QBFR10	Brown Bootlace Ferrule Single 10mm	10mm ²	12mm	4.6mm	Brown	100

