Riviera Oil Filled Radiator 0.7, 1.5 and 2.0 kW





p.120

0.7 kW model

1.5 and 2.0 kW model

Usage

Portable heater for home and office use.

Features and Benefits

- Oil filled radiator providing a silent gentle heating solution
- Neon element on indicator
- Moulded handle
- This product is only suitable for well insulated spaces or occasional use

0.7 kW model

- 1 power setting 700 W, adjustable thermostatic control
- 7 fins
- Floor standing on stationary feet


1.5 kW model

- 3 power settings
 (600, 900 and 1500 W)
 adjustable thermostatic control
- 7 fins
- Floor standing with smooth rolling castors for easy movement
- Tip over protection
- Cord cable storage

2.0 kW model

- 3 power settings (800, 1200 and 2000 W), adjustable thermostatic control
- 24 hour segment timer
- 9 fins
- Floor standing with smooth rolling castors for easy movement
- Tip over protection
- Cord cable storage

Product Code	Power (kW)	Timer	Current (amps)
RAD07Y	0.7	No	3
RAD15Y	1.5	No	6.5
RAD20TY	2.0	Yes	9



*Line diagram for 1.5 and 2.0 kW models only.

Outer Casing Metal

Controls

Thermostat dial.

2.0 kW model only:

24 hour segment timer with 15 minute interval time slots. Switch to select on all the time or timed operation. Push segments out for the time interval heater is to be timed on. Push segments in for the time interval heater is to be timed off.

Safety

Overheat temperature protection.

IP Rating IPXO

Electrical Connection

Supplied with a pre-wired (1.9m) black flex BS plug, cable entry to the right of the heater.

Class I

Approvals CE

Standard Warranty

1 year parts or replacement warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)*	Weight (kg)
RAD07Y	380	310	100	3.6
RAD15Y	690	385	160	9.8
RAD20TY	690	465	160	11.8

*Depth excluding feet, depth including feet 240mm for 1.5 and 2.0 kW versions and 140mm for 0.7 kW version.