



A

Dimensions



SMARTFIT CONNECTIVITY

Key Features

- Phased shutdown shower with digital numerical display and chrome accent controls
- SmartFit multi-entry connectivity for ease of shower replacement/installation
- Push button Start/Stop operation with high, medium, low and cold rotary power selection
- Rotary flow/temperature control
- 5 spray-mode shower head with easy rub-clean nozzles
- 500mm chrome riser rail with variable fixing brackets
- 1.5 metre anti-kink flexible shower hose, push-button adjustable handset clamp, soap dish and shower hose retaining ring

Technical Details

Model	RGS7	RGS8	RGS9	RGS10
EAN /Bar Code No.	5017084 535316	5017084 535002	5017084 535125	5017084 535217
Output (kW)	7.5	8.5	9.5	10.5
Current Rating (Amps) @240V	31.25	35.41	39.58	43.75
MCB Rating (Amps)	40	40	40	45
Energy Rating (Class)	A	A	A	A
Energy Rating (%)	39	39	39	39
Consumption (kWh/A)	478	478	479	478
Load Profile	XS			
Sound (dB)	15			
Operating Pressure psi/(bar)	15 (0.1) – 145 (10)			
Min. Running Pressure (l/min)	8	8	9	9
Water Connection	15mm compression or push-fit			
IP Rating	IPX4			
Approvals / Mark	BEAB & CE			
UK Guarantee (years)	3			



Product Range

Item Code:	Model No:	Description	kW
53535301	RGS7	Glow Electric Shower	7.5
53535001	RGS8	Glow Electric Shower	8.5
53535101	RGS9	Glow Electric Shower	9.5
53535201	RGS10	Glow Electric Shower	10.5

Packaging Details

Box dimensions (mm)	590 x 250 x 115
Shower gross weight (Kg)	3.4
Shower unit net weight (Kg)	2.8
Full pallet quantity	90
Showers per outer carton x layer x high	6 x 5 x 3