

■ SURFACE MOUNTING SOCKET OUTLETS - IP44

EUREKA Series


					522.					512.			
					STRAIGHT BOX		ANGLED BOX						
Poles	Hz.	Volt	Colour	h.	16A	32A	16A	32A					
					PG16/M20 □ 10/50	PG21/M25 □ 10/40	PG16/M20 □ 10/50	PG21/M25 □ 10/40					
2P+E	50/60	100-130		4	522.1650	522.3250	512.1650	512.3250					
	50/60	200-250		6	522.1653	522.3253	512.1653	512.3253					
	50/60	380-415		9	522.1658	522.3258	512.1658	512.3258					
	50/60	480-500		7									
	50/60	trasf.		12									
	>300-500	>50		2									
	c.c.	>50-250		3									
	c.c.	>250		8									
3P+E	50/60	100-130		4	522.1651	522.3251	512.1651	512.3251					
	50/60	200-250		9	522.1654	522.3254	512.1654	512.3254					
	50/60	380-415		6	522.1656	522.3256	512.1656	512.3256					
	60	440-460		11									
	50/60	480-500		7									
	50/60	600-690		5									
	50/60	380/440		3									
	100-300	>50		10									
>300-500	>50		2										
3P+N+E	50/60	100-130		4	522.1652	522.3252	512.1652	512.3252					
	50/60	208-250		9	522.1655	522.3255	512.1655	512.3255					
	50/60	346-415		6	522.1657	522.3257	512.1657	512.3257					
	50/60	480-500		7									
	50/60	600-690		5									
	60	440-460		11									

OPTIMA-BASE Series

OPTIMA-TOP Series

				513.				513.			
				STRAIGHT BOX		ANGLED BOX		SAFE-IN	FAST WIRING		
Poles	Hz.	Volt	Colour	16A	32A	16A	32A	16A	16A	32A	
				M20/M25 □ 10/40	M32 □ 1/10	M20/M25 □ 10/40	M32 □ 1/10	M20/M25 □ 10/40	M20/M25 □ 10/40	M32 □ 1/10	
2P+E	50/60	100-130		513.1650	513.3250	513.1650T	513.3250T	513.1650TH	513.1650TF	513.3250TF	
	50/60	200-250		513.1653	513.3253	513.1653T	513.3253T	513.1653TH	513.1653TF	513.3253TF	
	50/60	380-415				513.1658T	513.3258T	513.1658TH	513.1658TF	513.3258TF	
	50/60	480-500				513.16536T	513.32536T				
	50/60	trasf.				513.16533T	513.32533T				
	>300-500	>50				513.16532T	513.32532T				
	c.c.	>50-250				513.16534T	513.32534T				
	c.c.	>250				513.16538T	513.32538T				
	50/60	100-130		4			513.1651T	513.3251T			
	50/60	200-250		9			513.1654T	513.3254T	513.1654TH	513.1654TF	513.3254TF
3P+E	50/60	380-415		513.1656	513.3256	513.1656T	513.3256T	513.1656TH	513.1656TF	513.3256TF	
	60	440-460				513.16565T	513.32565T				
	50/60	480-500				513.16566T	513.32566T				
	50/60	600-690				513.16567T	513.32567T				
	50/60	380/440		3			513.16564T	513.32564T			
	100-300	>50		10			513.16561T	513.32561T			
	>300-500	>50		2			513.16562T	513.32562T			
	50/60	100-130		4			513.1652T	513.3252T			
	50/60	208-250		9			513.1655T	513.3255T			
	50/60	346-415		6	513.1657	513.3257	513.1657T	513.3257T	513.1657TH	513.1657TF	513.3257TF
3P+N+E	50/60	480-500				513.16576T	513.32576T				
	50/60	600-690				513.16577T	513.32577T				
	60	440-460		11			513.16575T	513.32575T			
	50/60	380/440		3			513.16574T	513.32574T			
	>300-500	>50		2			513.16572T	513.32572T			

Rated operating voltage >50V
- Approvals: from page 561



More information on page 36

■ Versions also available in a metric cable inlet.
For ordering add M after the first three digits
Example: 522.M1650

OPTIMA-BASE Series and OPTIMA-TOP Series IP44:
standard supply cable sleeve




■ SURFACE MOUNTING SOCKET OUTLETS - IP66/IP67

EUREKA Series

					527.			517.		
					STRAIGHT BOX		ANGLED BOX			
Poles	Hz.	Volt	Colour	h.	16A	32A	16A	32A		
					PG16/M20 □ 10/50	PG21/M25 □ 10/40	PG16/M20 □ 10/50 ⁽¹⁾	PG21/M25 □ 10/40		
2P+E	50/60	100-130		4	527.1650	527.3250	517.1650	517.3250		
	50/60	200-250		6	527.1653	527.3253	517.1653	517.3253		
	50/60	380-415		9	527.1658	527.3258	517.1658	517.3258		
	50/60	480-500		7						
	50/60	trasf.		12						
	>300-500	>50		2						
	c.c.	>50-250		3						
	c.c.	>250		8						
3P+E	50/60	100-130		4	527.1651	527.3251	517.1651	517.3251		
	50/60	200-250		9	527.1654	527.3254	517.1654	517.3254		
	50/60	380-415		6	527.1656	527.3256	517.1656	517.3256		
	60	440-460		11						
	50/60	480-500		7						
	50/60	600-690		5						
	50/60	380/440		3						
	100-300	>50		10						
>300-500	>50		2							
3P+N+E	50/60	100-130		4	527.1652	527.3252	517.1652	517.3252		
	50/60	208-250		9	527.1655	527.3255	517.1655	517.3255		
	50/60	346-415		6	527.1657	527.3257	517.1657	517.3257		
	50/60	480-500		7						
	50/60	600-690		5						
	60	440-460		11						

⁽¹⁾ 3P+N+E= □ 10/40

Rated operating voltage >50V
- Approvals: from page 561



More information on page 36

■ Versions also available in a metric cable inlet.
For ordering add M after the first three digits
Example: 522.M1650

OPTIMA-TOP Series

518.		SAFE-IN			FAST WIRING		515.	
16A	32A	16A	16A	32A	63A	125A		
M20/M25 □ 10/40	M32 □ 1/10	M20/M25 □ 10/40	M20/M25 □ 10/40	M32 □ 1/10	PG29/M32 □ 6/12	PG48/M63 □ 1/8		
518.1650T	518.3250T	518.1650TH	518.1650TF	518.3250TF	515.6350			
518.1653T	518.3253T	518.1653TH	518.1653TF	518.3253TF	515.6353	515.12553		
518.1658T	518.3258T	518.1658TH	518.1658TF	518.3258TF	515.6358			
518.16536T	518.32536T				515.63536			
518.16533T	518.32533T				515.63533			
518.16532T	518.32532T							
518.16534T	518.32534T				515.63534			
518.16538T	518.32538T				515.63538			
518.1651T	518.3251T				515.6351	515.12551		
518.1654T	518.3254T	518.1654TH	518.1654TF	518.3254TF	515.6354	515.12554		
518.1656T	518.3256T	518.1656TH	518.1656TF	518.3256TF	515.6356	515.12556		
518.16565T	518.32565T				515.63565	515.125565		
518.16566T	518.32566T				515.63566	515.125566		
518.16567T	518.32567T				515.63567	515.125567		
518.16564T	518.32564T			518.32564TF				
518.16561T	518.32561T							
518.16562T	518.32562T							
518.1652T	518.3252T				515.6352	515.12552		
518.1655T	518.3255T				515.6355	515.12555		
518.1657T	518.3257T	518.1657TH	518.1657TF	518.3257TF	515.6357	515.12557		
518.16576T	518.32576T				515.63576	515.125576		
518.16577T	518.32577T				515.63577	515.125577		
518.16575T	518.32575T				515.63575	515.125575		
518.16574T	518.32574T							
518.16572T	518.32572T							

