




## ENOLA ROUND M

outdoor LED surface-mounted ceiling light anthracite

The ENOLA SQUARE and ROUND light series have a purist style, consisting of a cylindrical or square aluminium construction fitted with powerful LEDs. Thanks to the integrated CCT switch, the light colour can be altered between 3000 K and 4000 K on installation. Thanks to the integrated LED driver, the electrical connection for the light is made directly to the 230 V mains voltage. In order to cover as wide a range of applications as possible, you can opt for one or two-lamp wall lights or ceiling lights in round or square form and in different sizes. This light contains integrated LED light bulbs.



### TECHNICAL DATA

Item no.	1003427
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	0.2 Joule
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Lumen	840/960 lm
Colour temperature	3000/4000 Kelvin
Beam angle	38 °
Color	anthracite
CRI	90
Service life	30000 h
Risk Group	1
Height	12.5 cm
Diameter	10 cm

## Light Source

916566	
--------	---

## Accessories

1005206	ENOLA M , lens asymmetric
1003479	Spacer set , for the ENOLA SQUARE OUT and ROUND OUT ceiling lights in anthracite
1005205	ENOLA M , lens 20°
1005207	ENOLA M , reflector 60°

Net weight	0.739 kg
Gross weight	0.867 kg
BIG WHITE Page	829