



BRICK

outdoor recessed wall light, LED, 3000K, stainless steel, 230V, IP67, 850lm, 10W

With the BRICK LED recessed wall light, which is made of stainless steel and aluminium, the built-in LEDs are covered by a glass sheet. The built-in reflector means that the light is output asymmetrically. The functional luminaire is connected directly to the 230V mains supply. With IP65 protection class, the luminaire is suitable for outdoor use. A mounting pot is included in the delivery for simple assembly. This luminaire contains built-in LED lamps.

TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 233660 |
| Number of different light outlets | 1 |
| IP Code | IP 65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 144 mA |
| Safety class | I |
| Wattage | 9.5 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 850 lm |
| Colour temperature | 3000 Kelvin |
| Color | stainless steel |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 25000 h |
| Length | 21 cm |
| Width | 9.1 cm |

Light Source

| | |
|--------|---|
| 916633 |  |
|--------|---|

| | |
|----------------------------|----------|
| Depth | 9.3 cm |
| Net weight | 1.756 kg |
| Gross weight | 1.844 kg |
| Shape of cut-out | square |
| Installation length | 19.6 cm |
| Installation width | 8.5 cm |
| Installation depth | 10.3 cm |
| BIG WHITE Page | 825 |