

## Zen Spa 100°C

2 in 1 Boiling and Chilled Tap  
3 and 6 litre boiling water tank



### Usage

The Zen Spa is a 2 in 1 hot and cold drinks station.

### Features and Benefits

- All of the features and benefits of the Zen Solo plus cold (ambient) or chilled drinking water from a single tap
- Commercial specification available in 3 and 6L models
- Energy efficient boiling water tank - costs just 4 p a day, based on standing losses 17 W. Electricity cost 10 p/ kWh.
- Modular solution allows you to tailor the tap to your individual requirements
- Cold (ambient) drinking water models connect directly to the incoming water supply
- Chilled drinking water models include a Sapphire undersink chiller (page 26)
- High quality cold drinking water filter supplied (F1T) (page 34)
- If you are in a hard scale area you may also need a scale filter on the inlet side of the boiling tank F5SST or F4SST depending on degree of scale (page 34)
- 6L model comprises 2 x 3 litre boiling water tanks with linking kit
- Recovery Rate  
100 cups/ 70 mugs per hour based on 167 ml cup and 250 ml mug
- Double recovery rate for 6 litre model

p.16



### Zen Spa Packages

Product Code	Description
SPA3L	Zen Spa 100°C Tap 3L Boiling and Ambient
SPA6L	Zen Spa 100°C Tap 6L Boiling and Ambient
SPA3LUC1	Zen Spa 100°C Tap 3L Boiling and Chilled, 3L initial draw off
SPA6LUC1	Zen Spa 100°C Tap 6L Boiling and Chilled, 3L initial draw off

Product Code	Capacity (litres)	Heat Up Time (mins)	Standing Loss (kWh/day)*
SPA3L all models	3	13	0.42 17 W
SPA6L all models	6	13	0.84 34 W

\* Standing loss figures are for the boiling tank only.

The 6 litre model comprises 2 x 3L tanks. Costs 8 p a day for 2 x 3L tanks.



\*\* Sapphire Undersink Chiller specifications see page 26

**Boiling Specification**

**Outer Casing**

Tap-polished chrome finish as standard  
Other tap finishes available at additional cost (page 13)  
Tank-durable high impact PC/ ABS

**Water Tank**

High quality grade 316L stainless steel

**Heating Element**

Incoloy

**Thermostat**

Electronic to control water up to boiling point

**Insulation**

Highly efficient aerogel thermal insulation

**Initial Draw off**

16 cups/ 11 mugs based on 167 ml cup and 250 ml mug.  
Double draw off for 6 litre model.

**Safety**

Overheat temperature protection (manual re-set).

Safety lock mechanism.

Supplied expansion vessel and pressure relief valve must be fitted.

**IP Rating**

IPX1

**Installation**

This appliance must be installed in a frost free environment.  
Required hole diameter for mounting tap 32mm – fits in a standard sink.  
Sink/counter top up to 50mm thick.

The dispensed water temperature can be adjusted down to 98°C on installation if required.

**Plumbing**

Must be installed by a suitably qualified person.

Intended for connection to the mains water supply.

Minimum water pressure 1 bar.  
Maximum water pressure 4.2 bar.  
If higher than this a pressure reducing valve may be required.

Supplied expansion vessel and pressure relief valve must be fitted.

**Electrical Connection**

Installation must comply with current IEE wiring regulations.

Supplied with a pre-wired (1m) BS plug.

**Approvals**

CE  
WRAS (98°C model only)

**Standard Warranty**

2 years parts or replacement warranty.

Product Code	Height (mm)	Width (mm)	Depth (mm)	Weight (kg)	
				Empty	Full
ZEN Spa Tap (all models)	320	224	56	1.6	–
ZEN Spa 3L Tank	459	181	220	5.8	8.8