

















ROOMS





WARRANTY

DELIVERY

COMMERCIAL RANGE





Diffuser

BACKLIT PANEL PRO




Order Code: PNL077-KIT01

Photometric Data		
Flicker Free	Yes	
Colour Rendering Index (CRI)	80-89	
Lumens	3100	
LPW (lm/W)	111	
Colour Temperature (K)	5000 - 5000	
SDCM	<5	
Beam Angle (°)	120 × 120	
UGR	<22	
UGR in Small Room (10m x 5m)	<19	
Light Distribution	Symmetric	
Photobiological Risk Group	0	
Lens / Reflector	Diffuser lens/optic/panel	

Life Data		
Rated Life @ 25°C (Hrs)	50000	
Rated Life L80/B50 @ 25°C	50000	

Electrical Data	
Input (W)	28
Input (V)±10%	220 - 240
Voltage Type	AC
Input Current (A)	0.14
Power Factor	0.95
THD (%)	<10
No. Per C16 Breaker	42
Energy Efficiency Class (EEC)	A++, A+, A (LED)
Electrical Class	II
Short Circuit Protection	Yes
Thermal Overload Protection	Yes
Type of Wiring	Suitable for Through Wiring
Non-dimmable	Yes
LED Nominal Current	750 - 750

Physical Data	
Degree of Protection (IP)	IP44
Housing Colour	White
Housing Material	Steel
Length (mm)	595
Width (mm)	595
Height/Depth (mm)	35
Weight (kg)	1.6
Warranty (year)	5
Case Material	Steel
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Cutout Height for Recess Mount (mm)	75
Cutout Length for Recess Mount (mm)	575
Cutout Width for Recess Mount (mm)	575
Lamp Type	LED Not Exchangeable
Cover Material	Opal Plastic
Impact Strength	IK03



25W Backlit Panel Pro, 600x600mm, 850, Driver



Order Code: PNL077-KIT01

Environmental Data		
Ambient Rated Temperature Range (°C)	-20 to 40	

Accessories	
EMG013 - 3W LED Emergency Downlight	
EMG018v2 - 3W Remote Emergency Pack	
ACS198 - Suspension Mount kit for Backlit Panels	
ACS199 - Recess Mount Kit for Backlit Panels	
ACS057 - Surface Mount Box for 600 x 600mm Panel	

Logistical Data		
Item Gross Weight (kg)	2.1	
Packaging Length (cm)	65.5	
Packaging Width (cm)	64.5	
Packaging Height (cm)	5.5	
Carton Quantity	5	
Carton Length (cm)	68	
Carton Width (cm)	66	
Carton Height (cm)	29	
Carton Gross Weight (kg)	11	