

Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A
Legend (ratings)	(II / 2) $\hat{=}$ Overvoltage category II / Pollution degree 2

Connection data

Connection technology	CAGE CLAMP®
Actuation type	Push-in
Connectable conductor materials	Copper
Solid conductor	0.5 ... 2.5 mm ² / 20 ... 16 AWG
Fine-stranded conductor	0.5 ... 2.5 mm ² / 20 ... 16 AWG
Strip length	9 ... 11 mm / 0.35 ... 0.43 Inch
Total number of connection points	2
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	8 mm / 0.315 Inch
Height	15.5 mm / 0.61 Inch
Depth	42 mm / 1.654 Inch

Material Data

Color	gray
Fire load	0.099 MJ
Weight	5 g



Commercial data

Packaging type	BOX
Country of origin	CH
GTIN	4044918818407


Country specific Approvals

Logo	Approval	Certificate name
	CSA DEKRA Certification B.V.	1053495
	VDE VDE Prüf- und Zertifizierungsinstitut	40022792

Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA
	BV Bureau Veritas S.A.	11914/C0 BV

UL-Approvals

Logo	Approval	Certificate name
	UL UL International Germany GmbH	CCA-DK No. 2527

Subject to changes.