

TKE/B 40/RD



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Brass nickel-plated
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP68 (5 bar 30 min), IP69
Surface	Nickel-plated
Thread type	M
Ø Connection thread D	40
Lead	1,5
Length screw-in thread L	8 mm
Key width SW	46 mm
Total length TL	44 mm - 55 mm
Type of cable anchorage	A
Install. torques fitting	20 N/m
Install. torques cap nut	20 N/m
Impact category	6
Order no. nickel-plated	10106235
Type	TKE/B 40/RD
Packing unit	1
ETIM-Classification	EC000441

Description:

UNIVERSAL OPTION Suitable for 32 or 40 mm. IP 68 Brass cable gland. EMSKV 40/ MFD 2 x 11 mm Tails and 1 x 6 mm Earth. Kit contains insert, locknut, blanking insert and MEM reduce.

26.03.2022

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk