

TKE/P 40/RD



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66, IP68 (5 bar 30 min)
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	40
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	46 mm
Total length TL	52 mm - 65 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	20 N/m
Install. torques cap nut	20 N/m
Impact category	4
Order no. RAL 7035	10106245
Type	TKE/P 40/RD
Packing unit	1
ETIM-Classification	EC000441

Description:

UNIVERSAL OPTION Suitable for 32 or 40 mm. IP 68 Plastic cable gland. ESKV 40/ MFD 2 x 25mm Tails and 1 x 16mm Earth, 1 KEM Adaptor 40 - 32mm. Kit contains insert, locknut, blanking insert and KEM reduce.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

02.07.2020

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk