



WMSS820



2 Gang Double Pole Switched Socket Dual Earth Outboard Rockers

## **Technical characteristics**

| Fixing mode<br>Main electrical features | flush-mounting                    |
|---|-----------------------------------|
|   |                                   |
| Nominal voltage                         | 250 V                             |
| Rated voltage                           | 220230 V AC                       |
| Rated current                           | 13 A                              |
| Rated current                           | 13 A                              |
| Dimensions                              |                                   |
| Depth                                   | 29,5 mm                           |
| Height                                  | 86 mm                             |
| Width                                   | 146 mm                            |
| Capacity                                |                                   |
| Number of modules                       | 0                                 |
| Cover, door                             |                                   |
| Cover                                   | Full cover plate                  |
| Materials                               |                                   |
| Colour                                  | white                             |
| Material                                | Urea-formaldehyde                 |
| Surface appearance                      | glossy                            |
| Type of surface treatment               | untreated                         |
| Colour syntax: Colour                   | white                             |
| Installation, mounting                  |                                   |
| mprint                                  | without imprint                   |
| Connection                              |                                   |
| Type of connection                      | screw                             |
| Cable                                   |                                   |
| Wiring                                  | with double earth connection      |
| Scope of delivery                       |                                   |
| Component                               | with 2 fixing screws M3.5 x 30 mm |
| Safety                                  |                                   |
| Protection index IP                     | IP20                              |
| Protection                              | Enhanced contact protection       |
| dentification                           |                                   |