

ADVANCE2 System switched socket outlets with interlock >50V

SURFACE MOUNTING - IP44

ADVANCE2 Series

INDUSTRIAL
1
2
3
4



Poles	Hz.	Volt	Colour	h.	560. COMPACT WITHOUT FUSE HOLDER		562. COMPACT WITH FUSE HOLDER		567. LARGE WITH RAIL DIN (6 MODULES)	
					16A M25 1/12	32A M25 1/12	16A M25 1/12	32A M25 1/12	16A M25 1/4	32A M25 1/4
2P+E	50/60	100-130	Yellow	4	560.1670	560.3270	562.1670	562.3270	567.1670	567.3270
	50/60	200-250	Blue	6	560.1683	560.3283	562.1683	562.3283	567.1683	567.3283
	50/60	380-415	Red	9	560.1678	560.3278	562.1678	562.3278	567.1678	567.3278
	50/60	480-500	Grey	7	560.16836	560.32836	562.16836	562.32836	567.16836	567.32836
	50/60	trasf.	Grey	12	560.16833	560.32833	562.16833	562.32833	567.16833	567.32833
	>300-500	(1) >50	Green	2	560.16832	560.32832	562.16832	562.32832	567.16832	567.32832
	c.c.	(2) >50-250	Grey	3	560.16834	560.32834	562.16834	562.32834	567.16834	567.32834
3P+E	50/60	100-130	Yellow	4	560.1672	560.3272	562.1672	562.3272	567.1672	567.3272
	50/60	200-250	Blue	9	560.1674	560.3274	562.1674	562.3274	567.1674	567.3274
	50/60	380-415	Red	6	560.1686	560.3286	562.1686	562.3286	567.1686	567.3286
	60	440-460	Red	11	560.16865	560.32865	562.16865	562.32865	567.16865	567.32865
	50/60	480-500	Grey	7	560.16866	560.32866	562.16866	562.32866	567.16866	567.32866
	50/60	(3) 600-690	Black	5	560.16867	560.32867	562.16867	562.32867	567.16867	567.32867
	50/60	380/440	Red	3	560.16864	560.32864	562.16864	562.32864	567.16864	567.32864
3P+N+E	100-300	(1) >50	Green	10	560.16861	560.32861	562.16861	562.32861	567.16861	567.32861
	>300-500	(1) >50	Green	2	560.16862	560.32862	562.16862	562.32862	567.16862	567.32862
	50/60	100-130	Yellow	4	560.1679	560.3279	562.1679	562.3279	567.1679	567.3279
	50/60	208-250	Blue	9	560.1675	560.3275	562.1675	562.3275	567.1675	567.3275
	50/60	346-415	Red	6	560.1687	560.3287	562.1687	562.3287	567.1687	567.3287
	50/60	480-500	Grey	7	560.16876	560.32876	562.16876	562.32876	567.16876	567.32876
	50/60	(3) 600-690	Black	5	560.16877	560.32877	562.16877	562.32877	567.16877	567.32877
3P+N+E	60	440-460	Red	11	560.16875	560.32875	562.16875	562.32875	567.16875	567.32875
	50/60	380/440	Red	3	560.16874	560.32874	562.16874	562.32874	567.16874	567.32874
	>300-500	(1) >50	Green	2	560.16872	560.32872	562.16872	562.32872	567.16872	567.32872



Rated voltage >50V

- Approvals: from page 561
- Switches as spare parts: page 188
- Supplied with stainless steel fixing screws.

(1) The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging

above 100 Hz; contact Scame Technical Service for further information.
 (2) When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

(3) Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

ADVANCE2 System
From page 110



ADVANCE2 System switched socket outlets with interlock >50V

SURFACE MOUNTING - IP66/IP67

ADVANCE2 Series

INDUSTRIAL 1 2 3 4



					COMPACT WITHOUT FUSE HOLDER		LARGE WITHOUT FUSE HOLDER
					16A	32A	63A
					M25 1/12	M25 1/12	M40 1/4
Poles	Hz.	Volt	Colour	h.			
2P+E	50/60	100-130	Yellow	4	561.1670	561.3270	561.6370
	50/60	200-250	Blue	6	561.1683	561.3283	561.6383
	50/60	380-415	Red	9	561.1678	561.3278	561.6378
	50/60	480-500	Grey	7	561.16836	561.32836	561.63836
	50/60	trasf.	Grey	12	561.16833	561.32833	561.63833
	>300-500	(1) >50	Green	2	561.16832	561.32832	
	c.c.	(2) >50-250	Grey	3	561.16834	561.32834	
	c.c.	(2) >250	Grey	8	561.16838	561.32838	
3P+E	50/60	100-130	Yellow	4	561.1672	561.3272	561.6372
	50/60	200-250	Blue	9	561.1674	561.3274	561.6374
	50/60	380-415	Red	6	561.1686	561.3286	561.6386
	60	440-460	Red	11	561.16865	561.32865	561.63865
	50/60	480-500	Grey	7	561.16866	561.32866	561.63866
	50/60	(3) 600-690	Black	5	561.16867	561.32867	561.63867
	50/60	380/440	Red	3	561.16864	561.32864	
	100-300	(1) >50	Green	10	561.16861	561.32861	
>300-500	(1) >50	Green	2	561.16862	561.32862		
3P+N+E	50/60	100-130	Yellow	4	561.1679	561.3279	561.6379
	50/60	208-250	Blue	9	561.1675	561.3275	561.6375
	50/60	346-415	Red	6	561.1687	561.3287	561.6387
	50/60	480-500	Grey	7	561.16876	561.32876	561.63876
	50/60	(3) 600-690	Black	5	561.16877	561.32877	561.63877
	60	440-460	Red	11	561.16875	561.32875	561.63875
	50/60	380/440	Red	3	561.16874	561.32874	
	>300-500	(1) >50	Green	2	561.16872	561.32872	



			COMPACT WITH FUSE HOLDER		LARGE WITH FUSE HOLDER	LARGE WITH RAIL DIN (6 MODULES)		
			16A	32A	63A	16A	32A	63A
			M25 1/12	M25 1/12	M40 1/4	M25 1/4	M25 1/4	M40 1/4
Poles	Hz.	Volt						
2P+E	50/60	100-130	563.1670	563.3270	563.6370	568.1670	568.3270	568.6370
	50/60	200-250	563.1683	563.3283	563.6383	568.1683	568.3283	568.6383
	50/60	380-415	563.1678	563.3278	563.6378(*)	568.1678	568.3278	568.6378(*)
	50/60	480-500	563.16836	563.32836		568.16836	568.32836	
	50/60	trasf.	563.16833	563.32833	563.63833	568.16833	568.32833	568.63833
	>300-500	(1) >50	563.16832	563.32832		568.16832	568.32832	
	c.c.	(2) >50-250	563.16834	563.32834		568.16834	568.32834	568.63834
	c.c.	(2) >250	563.16838	563.32838		568.16838	568.32838	568.63838
3P+E	50/60	100-130	563.1672	563.3272	563.6372	568.1672	568.3272	568.6372
	50/60	200-250	563.1674	563.3274	563.6374	568.1674	568.3274	568.6374
	50/60	380-415	563.1686	563.3286	563.6386(*)	568.1686	568.3286	568.6386(*)
	60	440-460	563.16865	563.32865		568.16865	568.32865	
	50/60	480-500	563.16866	563.32866		568.16866	568.32866	
	50/60	(3) 600-690	563.16867	563.32867		568.16867	568.32867	
	50/60	380/440	563.16864	563.32864		568.16864	568.32864	
	100-300	(1) >50	563.16861	563.32861		568.16861	568.32861	
>300-500	(1) >50	563.16862	563.32862		568.16862	568.32862		
3P+N+E	50/60	100-130	563.1679	563.3279	563.6379	568.1679	568.3279	568.6379
	50/60	208-250	563.1675	563.3275	563.6375	568.1675	568.3275	568.6375
	50/60	346-415	563.1687	563.3287	563.6387(*)	568.1687	568.3287	568.6387(*)
	50/60	480-500	563.16876	563.32876		568.16876	568.32876	
	50/60	(3) 600-690	563.16877	563.32877		568.16877	568.32877	
	60	440-460	563.16875	563.32875		568.16875	568.32875	
	50/60	380/440	563.16874	563.32874		568.16874	568.32874	
	>300-500	(1) >50	563.16872	563.32872		568.16872	568.32872	

(*) 400V only

Rated voltage >50V

- Approvals: from page 561
- Switches as spare parts: page 188
- Supplied with stainless steel fixing screws.

(1) The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging

above 100 Hz; contact Scame Technical Service for further information.
 (2) When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

(3) Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

